



Computing the radius of controllability for state space systems[☆]

Swanand R. Khare, Harish K. Pillai^{*}, Madhu N. Belur

Department of Electrical Engineering, Indian Institute of Technology Bombay, Powai, Mumbai, 400076, India

ARTICLE INFO

Article history:

Received 13 February 2011
 Received in revised form
 7 November 2011
 Accepted 20 November 2011
 Available online 5 January 2012

Keywords:

Radius of controllability
 Affinely structured matrices
 Structured Low Rank Approximation (SLRA)
 Structured Total Least Norm (STLN)

ABSTRACT

In this paper, we discuss the problem of computing the nearest uncontrollable system to a given control system represented by a matrix pair (A, B) . In order to do so, we construct a sequence of structured matrices from given system matrices A and B . Controllability of the pair (A, B) is equivalent to a condition on the null-space dimension of an appropriate matrix in this sequence. We show that the dimension of the reachability space is also related to the above condition. Further, it is shown that the nearest Structured Low Rank Approximation (SLRA) of this structured matrix corresponds to a nearest uncontrollable system to the pair (A, B) .

© 2011 Elsevier B.V. All rights reserved.

1. Introduction

Controllability of a system is a central concept of systems theory. Consider a system in state space representation as

$$\dot{x} = Ax + Bu \quad (1)$$

where $A \in \mathbb{R}^{g \times g}$, $B \in \mathbb{R}^{g \times p}$. The well known test for controllability is to check if the controllability matrix, $\mathcal{C}(A, B) = [B \ AB \ \dots \ A^{g-1}B]$, is full rank. Further, the Hautus test for controllability states that the matrix $H = [\lambda I - A \ B]$ is required to be full rank for all $\lambda \in \mathbb{C}$ for the system to be controllable (for further details, see [1]). All these tests answer the question of whether the system is controllable. However, knowing whether the system is controllable is often not enough. This is illustrated in the following example.

Example 1.1. Let the system be described as in (1) where $A = \begin{bmatrix} 10 & \epsilon \\ 1 & 0 \end{bmatrix}$ and $b = \begin{bmatrix} 0 \\ 1 \end{bmatrix}$. For any $\epsilon \neq 0$, the system (A, b) is controllable. However note that for very small ϵ such that $|\epsilon| > 0$, a small perturbation in the matrix A can make this system uncontrollable.

From the example above, it is clear that though the system is controllable for all $\epsilon \neq 0$, the numerical robustness for controllability changes with ϵ . In order to overcome this difficulty, attempts have been made to define a continuous metric for

checking controllability as opposed to the yes/no kind of discrete metric (see [2–5]). In [4], the distance between the given pair (A, B) and the set of all uncontrollable systems is shown to be same as

$$\min_{\lambda \in \mathbb{C}} \sigma_{\min} [\lambda I - AB] \quad (2)$$

where σ_{\min} denotes the smallest singular value of the matrix. A relation between the positive definite solution of a certain Riccati equation and the nearness to uncontrollability is proved in [6]. From this result, upper and lower bounds are derived for the distance to uncontrollability. The distance between the given system and the nearest uncontrollable system in real as well as complex cases is discussed in [7] along with some properties of the reachability Gramian. Various numerical algorithms have been considered to compute the lower and upper bounds for the distance to uncontrollability. See for instance [8–10]. A bisection method is developed in [11] to compute this distance. In [12], the algorithm proposed in [11] is improved with respect to computational cost. The improved algorithm is based on a trisection algorithm and a novel algorithm to extract eigenvalues of a matrix with Kronecker structure. The algorithm proposed in [11] has complexity $O(n^6)$ while the improved version in [12] has complexity $O(n^4)$ on average.

The real¹ radius of controllability or radius of controllability is defined as follows:

$$r_c = \min_{\Delta A \in \mathbb{R}^{g \times g}, \Delta B \in \mathbb{R}^{g \times p}} \{ \|\Delta A \ \Delta B\|_F \mid \text{the pair} \\ (A + \Delta A, B + \Delta B) \text{ is uncontrollable} \}. \quad (3)$$

[☆] This work was supported in part by SERC division, Department of Science and Technology, India.

^{*} Corresponding author.

E-mail address: hp@ee.iitb.ac.in (H.K. Pillai).

¹ The word *real* in the definition of real radius of controllability is emphasized to indicate that the perturbations that are allowed in the system matrices are real matrices. When the complex perturbations are allowed, the term is defined as the complex radius of controllability.

Remark 2.9. Another way to understand Definition 2.8 is as follows: given a pair (A, B) , there exists a ball of radius r with center at (A, B) where all pairs (\tilde{A}, \tilde{B}) in this ball have rank of $\mathcal{C}(\tilde{A}, \tilde{B}) > g - k$. The supremum of such r is $r_c(k)$.

The real radius of controllability as defined in (3) (see [13]) is indeed the real radius of controllability of order 1, denoted as $r_c(1)$.

Using Theorem 2.3 we now give a procedure to compute the nearest uncontrollable pair to the given pair (A, B) . If the pair (A, B) is controllable, then $d_{g-1} = gp - g$ and hence the dimension of the reachability space is g . Fixing some matrix norm, if one finds the nearest matrix to X_{g-1} that preserves the same structure as that of X_{g-1} (namely the block Toeplitz structure as in (5)) but has lower rank than X_{g-1} , then one would have effectively found the closest uncontrollable system to the given system. Such problems of finding a lower rank matrix that preserves a certain structure have been investigated in the literature and goes under the name of Structured Low Rank Approximation, abbreviated as SLRA (see for instance [19,20]). Thus we have the following theorem.

Theorem 2.10. Let the given controllable system be represented as in (1) where $A \in \mathbb{R}^{g \times g}$ and $B \in \mathbb{R}^{g \times p}$. Construct the sequence of structured matrices $\{X_i\}_{i=0,1,2,\dots}$ as in (4). Let \tilde{X}_{g-1} be the nearest SLRA of X_{g-1} in the Frobenius norm. Construct \tilde{A} and \tilde{B} from \tilde{X}_{g-1} . Then

$$r_c(1) = \left\| [A \ B] - \begin{bmatrix} \tilde{A} & \tilde{B} \end{bmatrix} \right\|_F, \quad (18)$$

where $r_c(1)$ is the radius of controllability of order 1.

Computation of $r_c(k)$ for $k > 1$

For computing $r_c(k)$ for $k > 1$ we require a generalization of Theorem 2.3 which we state below.

Lemma 2.11. Consider a pair (A, B) with $A \in \mathbb{R}^{g \times g}$ and $B \in \mathbb{R}^{g \times p}$. For a given j define $\mathcal{C}_j(A, B) = [B \ AB \ \dots \ A^{j-1}B]$. Construct the sequence of structured matrices X_i as in (4). Let $d_i = \dim(\text{null}(X_i))$. Then $\dim(\text{null}(\mathcal{C}_i(A, B))) = d_{i-1}$.

Proof. See the proof of Theorem 2.3. \square

In order to give a procedure to compute $r_c(k)$, we consider single-input and multi-input systems separately.

Single-input case

Let a controllable pair (A, B) be given where $A \in \mathbb{R}^{g \times g}$ and $B \in \mathbb{R}^{g \times 1}$. We compute the nearest SLRA of X_{g-1} and by Theorem 2.10 we obtain the corresponding nearest uncontrollable pair (\tilde{A}, \tilde{B}) . The dimension of the reachability subspace for the pair (\tilde{A}, \tilde{B}) turns out to be $g - 1$. If we want to compute the nearest uncontrollable pair such that the dimension of the reachability space is at most $g - k$ where $1 \leq k \leq g - 1$, it is enough to compute the SLRA of the matrix X_{g-k} . By Lemma 2.11 the dimension of the subspace $\mathcal{C}_{g-k+1}(A, B)$ of the pair (A, B) is $g - k + 1$ (assuming (A, B) is a controllable pair). Therefore by finding the nearest SLRA of X_{g-k} , one effectively reduces the dimension of the subspace $\mathcal{C}_{g-k+1}(\tilde{A}, \tilde{B})$ to be strictly less than $g - k + 1$. As it is a single input system, this in fact forces the reachability space of (\tilde{A}, \tilde{B}) to be at most $g - k$ dimensional.

Multi-input case

For a single-input system there is only one controllability index whereas for a multi-input system there are several controllability indices. This complicates the computation of $r_c(k)$ for $k > 1$. Consider a pair (A, B) with $A \in \mathbb{R}^{g \times g}$ and $B \in \mathbb{R}^{g \times p}$. Let $\kappa_1, \kappa_2, \dots, \kappa_p$ be the controllability indices as defined in (13). For a controllable pair (A, B) , the dimension of $\mathcal{C}_i(A, B) = g$ for all $i > \kappa_1$. Before giving a procedure to compute $r_c(k)$, we prove the following lemma which is useful.

Lemma 2.12. Let (A, B) be given system with $A \in \mathbb{R}^{g \times g}$ and $B \in \mathbb{R}^{g \times p}$ such that the dimension of the reachability space of the pair (A, B) is $g - k$. Construct the sequence of structured matrices as in (4). Let $\kappa_1, \kappa_2, \dots, \kappa_p$ be the controllability indices as in (13). Then $d_i = (i + 1)p - g + k$ for all $i > \kappa_1$.

Proof. Since the dimension of the reachability space for the pair (A, B) is $g - k$, from Theorem 2.3 we get $d_{g-1} = gp - g + k$. By Lemma 2.11, $\dim(\text{null}(\mathcal{C}_i(A, B))) = d_i$ for $i \geq 1$. Clearly $\dim(\text{range}(\mathcal{C}_i(A, B))) = g - k$ for all $i > \kappa_1$. Therefore $\dim(\text{null}(\mathcal{C}_i(A, B))) = d_i = (i + 1)p - g + k$ for all $i > \kappa_1$. \square

In order to compute $r_c(k)$ when $k = 1$, we compute the nearest SLRA to X_{g-1} , say \tilde{X}_{g-1} . Construct the pair (\tilde{A}, \tilde{B}) from \tilde{X}_{g-1} . Then the pair (\tilde{A}, \tilde{B}) is the nearest uncontrollable pair to (A, B) . For $r_c(k)$ with $k > 1$, we cannot use an approach similar to that in the single-input case due to Lemma 2.12. We construct X_{g-1} and compute the nearest SLRA to X_{g-1} , denoted as \tilde{X}_{g-1} , that sets k singular values of \tilde{X}_{g-1} to zero. We construct the pair (\tilde{A}, \tilde{B}) from \tilde{X}_{g-1} . Then from Lemma 2.12, we know that the dimension of the reachability space for the pair (\tilde{A}, \tilde{B}) is $g - k$.

3. SLRA and algorithm

In this section, we first state the problem of computing the nearest SLRA of a given affinely structured matrix. Then we formulate the problem of computing the nearest uncontrollable system as the SLRA problem. Finally we discuss a numerical algorithm to compute the nearest SLRA of a given matrix. Before we proceed further with the problem formulation we make an observation.

Remark 3.1. We obtain the sequence of structured matrices from the pair (A, B) as in (4). The set of structured matrices (to which X_i belongs for each i) of size $(i + 2)g \times (i + 1)(g + p)$ is an affine space of dimension $g(g + p)$. For example, when $g = 3$, $p = 1$, $i = 1$, the dimension of the affine space is 12.

SLRA formulation. For a given structure of matrices, let $\Omega \subset \mathbb{R}^{p \times q}$ denote the set of all structured matrices. Now we define the problem of computing the nearest SLRA as in [19].

Problem statement 3.2. Given $\Omega \subset \mathbb{R}^{p \times q}$, the set of matrices with the given structure, and $X \in \Omega$ such that $\text{rank}(X) = k$ for $k \leq \min\{p, q\}$, find a matrix Y such that

$$\min_{Y \in \Omega, \text{rank}(Y)=k-1} \|X - Y\|_F.$$

3.1. An algorithm to compute the nearest SLRA

The problem of computing the nearest SLRA of a given structured matrix is well studied in the literature (see [19,20]). Here we adopt the method discussed in [21] to the structured matrices with the structure as described in Section 2. We explain the Structured Total Least Norm (STLN) algorithm in this subsection.

We describe the algorithm for a general affine structure. Let $\Omega \subset \mathbb{R}^{p \times q}$ be the set of all structured matrices with a given affine structure. Thus Ω is an affine space in $\mathbb{R}^{p \times q}$. For a given $Z \in \Omega$ with rank r we need to compute the nearest $Y \in \Omega$ with rank $r - 1$. We partition $Z = [Z_1 \ z]$, where $Z_1 \in \mathbb{R}^{p \times (q-1)}$ and $z \in \mathbb{R}^{p \times 1}$. Then the problem of computing the nearest SLRA can be formulated as

$$\min_{H, h, x} \|[H \ h]\|_F \quad \text{subject to } (Z_1 + H)x = (z + h) \quad (19)$$

where $H \in \mathbb{R}^{p \times (q-1)}$, $h \in \mathbb{R}^{p \times 1}$ are such that $[H \ h]$ belongs to the linear space corresponding to Ω and $x \in \mathbb{R}^{q-1}$. Note that this problem is similar to the Total Least Squares (TLS) problem with

Table 1Comparison of radius of controllability for different values of $t \in \mathbb{R}$ (Example 4.1).

t	10	2	1.7	1.2	1.1	1	10^{-1}	10^{-3}	10^{-5}
r_c	0.2165	0.718	0.769	0.8596	0.8777	0.8954	$9.127e - 2$	$9.129e - 4$	$9.129e - 6$

an additional constraint on the structure of perturbation matrices H and h , hence the name Structured Total Least Squares (STLS) problem.

Let $\{B_1, B_2, \dots, B_N\}$ be a basis for the linear space corresponding to Ω . Let $\Delta Z = [H \ h]$ be such that ΔZ belongs to the linear space corresponding to Ω . Let $\alpha = [\alpha_1 \ \alpha_2 \ \dots \ \alpha_N]^T \in \mathbb{R}^N$ be coordinates of ΔZ with respect to the basis $B = \{B_1, B_2, \dots, B_N\}$. Then we have $\Delta Z = \sum_{i=1}^N \alpha_i B_i$. We call α the representation of ΔZ . Let $P \in \mathbb{R}^{p \times N}$ be a matrix such that $h = P\alpha$. Then the structured minimization problem as in (19) can be stated as follows:

$$\min_{\alpha, x} \|D\alpha\|_2 \quad \text{subject to } \hat{r} = 0 \quad (20)$$

where the structured residual $\hat{r} = \hat{r}(\alpha, x) = z + P\alpha - (Z_1 + H)x$ and D is a positive definite weight matrix. If B is an orthonormal basis, the weight matrix can be chosen to be $D = I_N$. The above problem can be solved using the penalty method in the following way.

$$\min_{\alpha, x} \left\| \begin{bmatrix} \omega \hat{r}(\alpha, x) \\ \alpha \end{bmatrix} \right\|_2, \quad (21)$$

where ω is a very large positive constant. Typically in numerical simulations ω is taken in the range of 10^8 – 10^{10} . As proposed in [21], we linearize the structured residual as follows:

$$\begin{aligned} \hat{r}(\alpha + \Delta\alpha, x + \Delta x) &= z + P(\alpha + \Delta\alpha) \\ &\quad - (Z_1 + H + \Delta H)(x + \Delta x) \\ &\approx z + P\alpha + P\Delta\alpha - (Z_1 + H)x \\ &\quad - (Z_1 + H)\Delta x - \Delta Hx. \end{aligned}$$

Let $S \in \mathbb{R}^{p \times N}$ be a matrix such that $S\Delta\alpha = \Delta Hx$. The structure of S is similar to that of H . The entries in S depend on the entries of the vector x . Then (21) can be approximated by

$$\min_{\Delta\alpha, \Delta x} \left\| \begin{bmatrix} \omega(S - P) & \omega(Z_1 + H) \\ I_N & 0 \end{bmatrix} \begin{bmatrix} \Delta\alpha \\ \Delta x \end{bmatrix} + \begin{bmatrix} -\omega \hat{r} \\ \alpha \end{bmatrix} \right\|_2. \quad (22)$$

We now summarize the algorithm.

Algorithm 3.3. STLN Algorithm

Input: Matrices Z_1 , z and tolerance ϵ .

Output: Error matrix ΔX such that $\Delta X \in \Omega$, vector x and STLN error

Step 1: Choose a large number ω .

Step 2: Set $H = 0$, $h = 0$ and find x from $\min_x \|z - Z_1 x\|_2$ and S from x .

Step 3: Set $\hat{r} = z - Z_1 x$.

Step 4: Repeat

- Solve the minimization problem in (22).
- Set $x := x + \Delta x$, $\alpha := \alpha + \Delta\alpha$.
- Construct $[H \ h]$ from α and S from x .
- Compute $\hat{r} = (z + P\alpha) - (Z_1 + H)x$.

until $(\|\Delta x\|, \|\Delta\alpha\| \leq \epsilon)$.

Remark 3.4. The function we are trying to minimize is not a convex function and hence we do not guarantee the global minimizer. However this STLN formulation is equivalent to the TLS (Total Least Squares) formulation when there is no structure imposed on the residual. In this case, the solution obtained by the STLN algorithm is same as that obtained using TLS methods (see [21]).

The computational complexity of Algorithm 3.3 depends on the step (4a) where the least squares problem in (22) is solved. The matrix S is a specially structured matrix and it is shown in [21] that QR factorization of this structured matrix can be computed efficiently.

3.2. An algorithm to compute the nearest uncontrollable pair

In this subsection, we give an algorithm to compute the real radius of controllability for a given pair (A, B) . The algorithm that we present is based on Theorems 2.3 and 2.10 and Algorithm 3.3.

Algorithm 3.5. Algorithm to compute the real radius of controllability $r_c(1)$

Input: Given a pair (A, B) such that $A \in \mathbb{R}^{g \times g}$, $B \in \mathbb{R}^{g \times p}$.

Output: The nearest pair (\tilde{A}, \tilde{B}) and the real radius of controllability $r_c(1)$.

Step 1: Construct X_{g-1} as in (4).

Step 2: Compute the nearest SLRA \tilde{X}_{g-1} of X_{g-1} using Algorithm 3.3.

Step 3: Construct (\tilde{A}, \tilde{B}) from \tilde{X}_{g-1} .

Step 4: Compute $r_c(1) = \left\| \begin{bmatrix} \tilde{A} & \tilde{B} \end{bmatrix} - [A \ B] \right\|_F$.

For the specific case of single-input systems, (i.e., $B \in \mathbb{R}^{g \times 1}$), one can calculate $r_c(k)$ for any $k \leq g - 1$ by using the above algorithm. In order to do so, we construct X_{g-k} in Step 1 of the algorithm and proceed with the subsequent steps of the algorithm with X_{g-k} instead of X_{g-1} . Then the pair (\tilde{A}, \tilde{B}) obtained from \tilde{X}_{g-k} has the reachability space dimension equal to $g - k$. However, for multi-input systems, the above algorithm would not calculate $r_c(k)$ for $k \geq 1$ (as discussed earlier).

Remark 3.6. The results presented in Section 2 hold true when the field under consideration is changed from \mathbb{R} to \mathbb{C} . Further, the algorithm presented in Section 3 can be easily generalized for complex field (see [21]). Hence using our approach, we can easily compute the complex radius of controllability also.

Remark 3.7. Note that Algorithm 3.5 depends on Algorithm 3.3 to compute the nearest SLRA. Algorithm 3.3 is known to converge to a local minimizer but the guarantee of convergence to a global minimizer is not assured. Therefore, we obtain an upper bound while computing the real radius of controllability. However through the numerical examples in the following section, we observe that the proposed approach estimates of the real radius of controllability are better than the ones available in the literature.

4. Numerical examples

In this section, we discuss some numerical examples where the proposed algorithm in the previous section is applied.

Example 4.1. The following pair (A, B) has been studied in [22]:

$$A = \begin{bmatrix} -1 & -1 & 0 \\ 1 & -1 & 0 \\ 0 & 0 & -3 \end{bmatrix} \text{ and } B = \begin{bmatrix} 0 \\ t \\ 1 \end{bmatrix} \text{ where } t \in \mathbb{R}. \text{ Clearly, as } t \rightarrow 0 \text{ the pair } (A, B) \text{ gradually loses controllability. In Table 1,}$$

Table 2
Radii of controllability for different dimensions of reachability spaces (Example 4.3).

Dimension (k) of the reachability space	3	2	1
$r_c(k)$	0.4607	0.5658	0.9996

we compare the values of real radius of controllability obtained for different values of $t \in \mathbb{R}$.

When the parameter $t = 10$, the perturbation matrices ΔA and ΔB such that the pair $(A + \Delta A, B + \Delta B)$ is uncontrollable are as given below. One can check that $[\Delta A \ \Delta B]$ is rank one and has 2-norm (and the Frobenius norm): 0.216487.

$$\Delta A = \begin{bmatrix} -9.39222e - 11 & -1.86154e - 10 & -1.774895e - 11 \\ -9.008923e - 3 & -1.785553e - 2 & -1.702449e - 3 \\ 9.448684e - 2 & 1.872712e - 1 & 1.785553e - 2 \end{bmatrix}$$

$$\Delta B = \begin{bmatrix} 4.584664e - 11 \\ 4.397604e - 3 \\ -4.612268e - 2 \end{bmatrix}.$$

Note that the 2-norm of the perturbation matrix reported in [22] is 0.219866. For rank 2 perturbation matrices $[\Delta A \ \Delta B]$, the Frobenius norm is larger than the 2-norm: this is reflected in the r_c values for smaller values of t when a pair of complex eigenvalues becomes uncontrollable in the perturbed system. See the following example for a similar situation and discussion about the choice of norm used in the definition.

Example 4.2. Consider the pair (A, B) that has been studied in [8,13] and [22, Example 4]

$$A = \begin{bmatrix} 1 & 1 & 1 \\ 0.1 & 3 & 5 \\ 0 & -1 & -1 \end{bmatrix}, \quad B = \begin{bmatrix} 1 \\ 0.1 \\ 0 \end{bmatrix}.$$

The real radius r_c of controllability obtained using our approach is 0.05734, and the perturbation matrices ΔA and ΔB are respectively

$$\begin{bmatrix} 5.8878e - 4 & 4.966e - 5 & -2.9287e - 5 \\ -1.684774e - 2 & -1.420985e - 3 & 8.380330e - 4 \\ -1.673060e - 2 & -1.411105e - 3 & 8.322061e - 4 \end{bmatrix} \quad \text{and}$$

$$\begin{bmatrix} -1.1427e - 3 \\ -1.575356e - 2 \\ -4.968473e - 2 \end{bmatrix}.$$

In [8], where, like in this paper, the Frobenius norm was used for defining the radius of controllability, the same value 0.05734 was reported as the radius of controllability. In [13], the 2-norm of the perturbation required for uncontrollability was reported as 0.0492: the real radius defined there uses the 2-norm. The 2-norm of the above perturbation matrices obtained using our approach is 0.0564. On the other hand, the Frobenius norm of the perturbation matrix reported in [13] is 0.0696: this fact underlines the crucial (and quite unsurprising) dependence of the ‘closest’ uncontrollable pair on the choice of the matrix norm of the perturbation matrix in the definition of radius of controllability: this paper focuses on the Frobenius norm.

Table 3
Average number of iterations for various sizes (Example 4.4).

g	5	7	10	12	15	20
Average number of iterations	4.055	4.800	3.257	3.222	6.158	7.0122

Table 4
Radii of controllability for various sizes of the system (Example 4.5).

g	5	10	15	20
$r_c(1)$	0.4310	0.2281	0.1663	0.1312

Example 4.3. Consider a pair

$$A = \begin{bmatrix} 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \\ 0 & 1 & 0 & 1 \end{bmatrix}, \quad B = \begin{bmatrix} 0 \\ 0 \\ 0 \\ 1 \end{bmatrix}.$$

Clearly the dimension of the reachability space of this pair (A, B) is 4. In Table 2, we list the minimum norms of perturbation matrices that reduce the dimension of the corresponding perturbed system’s reachability space. As expected, the norm of the perturbation required is larger for a lower dimensional reachability space.

Example 4.4. In this example, we illustrate the convergence properties of the SLRA algorithm. In order to do this, we have considered 1000 randomly generated test examples for various sizes g of the pair (A, B) , with $A \in \mathbb{R}^{g \times g}$ and $B \in \mathbb{R}^{g \times 1}$. We note the average number of iterations required to compute the nearest SLRA and hence the radius controllability $r_c(1)$ for these cases (see Table 3).

Example 4.5. Let the pair (A, B) be given as

$$A = \begin{bmatrix} 0 & 1 & 0 & \dots & 0 \\ 0 & 0 & 1 & \dots & 0 \\ \vdots & & & \ddots & \vdots \\ 0 & 0 & \dots & & 1 \\ 1 & 0 & \dots & & 1 \end{bmatrix} \in \mathbb{R}^{g \times g}, \quad B = \begin{bmatrix} 0 \\ 0 \\ \vdots \\ 1 \end{bmatrix} \in \mathbb{R}^{g \times 1}.$$

In Table 4, we list $r_c(1)$ for various values of g : the distance to uncontrollability is expectedly decreasing as the size grows.

5. Conclusions

In this paper, we have given a numerical algorithm to compute the radius of controllability of a specified order for a given pair (A, B) . The approach discussed in this paper is different from the previous approaches to solve the problem. The problem of computing the radius of controllability is shown to be equivalent to the problem of computing the nearest SLRA of a certain structured matrix associated to the system described as in (1). We further solve the problem of computing the radius of controllability of order k , where k is the desired dimension of the reachability space of the perturbed system. The results proved here can be easily dualized to solve the corresponding problem of observability, namely computing the nearest unobservable system by considering the pair (A^T, C^T) .

Acknowledgment

This work was supported in part by SERC division, Department of Science and Technology, India.

References

- [1] T. Kailath, *Linear Systems*, Prentice-Hall Inc, Englewood Cliffs, N. J., 1980, 07632.
- [2] C.C. Paige, Properties of numerical algorithms related to computing controllability, *IEEE Transactions on Automatic Control* 26 (1) (1981) 130–138.
- [3] R. Eising, The distance between a system and the set of uncontrollable systems, *Lecture Notes in Control and Information Science*, Proceeding of MTNS 1983 (1984) 304–314.
- [4] R. Eising, Distance between controllable and uncontrollable, *Systems & Control Letters* 4 (1984) 263–264.
- [5] A.J. Laub, Numerical linear algebra aspects of control design computations, *IEEE Transactions on Automatic Control* 30 (2) (1985) 97–108.
- [6] P.M. Gahinet, Distance to the nearest uncontrollable pair and algebraic riccati equation, in: *Proceedings of the 29th Conference on Decision and Control*, Honolulu, USA, 1990, pp. 273–278.
- [7] D.L. Boley, W.S. Lu, Measuring how far a controllable system is from an uncontrollable one, *IEEE Transactions on Automatic Control* 31 (3) (1986) 249–251.
- [8] M. Wicks, R. DeCarlo, Computing the distance to an uncontrollable system, in: *Proceedings of the 28th IEEE Conference on Decision and Control*, Tampa, USA, 1989, pp. 2361–2366.
- [9] L. Elsner, C. He, An algorithm to compute distance to uncontrollability, *Systems & Control Letters* 17 (1991) 453–463.
- [10] C. He, Estimating the distance to uncontrollability: a fast method and a slow one, *Systems & Control Letters* 26 (1995) 275–281.
- [11] M. Gu, New methods for estimating the distance to uncontrollability, *SIAM Journal of Matrix Analysis and Applications* 21 (3) (2000) 989–1003.
- [12] M. Gu, E. Mengi, M.L. Overton, J. Xia, J. Zhu, Fast methods for estimating the distance to uncontrollability, *SIAM Journal of Matrix Analysis and Applications* 28 (2) (2006) 477–502.
- [13] G. Hu, E. Davison, Real controllability/stabilizability radius of LTI systems, *IEEE Transactions on Automatic Control* 49 (2) (2004) 254–258.
- [14] M. Karow, D. Kressner, On the structured distance to uncontrollability, *Systems & Control Letters* 58 (2009) 128–132.
- [15] D.S. Watkins, *Fundamentals of Matrix Computations*, second ed., John Wiley and Sons Publications, 2002.
- [16] D.L. Boley, The algebraic structure of pencils and block Toeplitz matrices, *Linear Algebra and Its Applications* 279 (1998) 255–279.
- [17] P.M.V. Dooren, The generalized eigenstructure problem in linear systems theory, *IEEE Transactions on Automatic Control* AC-26 (1981) 111–129.
- [18] W.M. Wonham, *Linear Multivariable Control: A Geometric Approach*, Springer Verlag, New York, 1979.
- [19] M.T. Chu, R.E. Funderlic, R.J. Plemmons, Structured low rank approximation, *Linear Algebra and Its Applications* 366 (2003) 157–172.
- [20] I. Markovski, Structured low rank approximation and its applications, *Automatica* 44 (2008) 891–909.
- [21] J.B. Rosen, H. Park, J. Glick, Total least norm formulation and solution for structured problems, *SIAM Journal of Matrix Analysis and Applications* 17 (1996) 110–126.
- [22] G. Hu, E.J. Davison, A real radius measure for controllability, in: *Proceedings of the American Control Conference*, Arlington, USA, 2001, pp. 3144–3148.