

SEMICONDUCTOR DEVICES

p - n Junctions: Part 2





M. B. Patil



mbpatil@ee.iitb.ac.in

www.ee.iitb.ac.in/~sequel



Department of Electrical Engineering
Indian Institute of Technology Bombay

pn junction under bias







- * With $V_a \approx 0.6$ V a substantial current flows. When V_a is increased further, the current increases rapidly.





- * With $V_a \approx 0.6$ V a substantial current flows. When V_a is increased further, the current increases rapidly.
- * When a reverse bias (i.e., $V_a < 0$, V) is applied, the diode blocks conduction, i.e., the current is negligibly small.



- * With $V_a \approx 0.6$ V a substantial current flows. When V_a is increased further, the current increases rapidly.
- * When a reverse bias (i.e., $V_a < 0$, V) is applied, the diode blocks conduction, i.e., the current is negligibly small.

We want to understand this “rectifying” behaviour.





- * With $V_a \approx 0.6$ V a substantial current flows. When V_a is increased further, the current increases rapidly.
- * When a reverse bias (i.e., $V_a < 0$, V) is applied, the diode blocks conduction, i.e., the current is negligibly small.

We want to understand this “rectifying” behaviour.

- * As we increase the forward bias, the current increases rapidly, and at some point, the device will get damaged because of overheating. For silicon diodes used in low-power applications, the forward voltage must be restricted to about 0.8 V.



(Note: Although we will show an applied forward/reverse bias with a battery, in practice, a diode is generally not directly connected to a battery.)

Where does the voltage drop?



Consider a *pn* junction in equilibrium ($V_a = 0$ V).



Where does the voltage drop?



Consider a *pn* junction in equilibrium ($V_a = 0$ V).

- * V_{contact}^p and V_{contact}^n are the voltage drops across the contact regions (which generally include heavily doped regions).



Where does the voltage drop?



Consider a *pn* junction in equilibrium ($V_a = 0$ V).

- * V_{contact}^p and V_{contact}^n are the voltage drops across the contact regions (which generally include heavily doped regions).
- * V_{contact}^p and V_{contact}^n remain constant irrespective of the applied voltage (to be discussed later).



Where does the voltage drop?



Consider a *pn* junction in equilibrium ($V_a = 0$ V).

- * V_{contact}^p and V_{contact}^n are the voltage drops across the contact regions (which generally include heavily doped regions).
- * V_{contact}^p and V_{contact}^n remain constant irrespective of the applied voltage (to be discussed later).
- * V_{neutral}^p and V_{neutral}^n are the voltage drops across the neutral *p* and *n* regions. In equilibrium, they are both zero.



Where does the voltage drop?





Consider a *pn* junction in equilibrium ($V_a = 0$ V).

- * V_{contact}^p and V_{contact}^n are the voltage drops across the contact regions (which generally include heavily doped regions).
- * V_{contact}^p and V_{contact}^n remain constant irrespective of the applied voltage (to be discussed later).
- * V_{neutral}^p and V_{neutral}^n are the voltage drops across the neutral *p* and *n* regions. In equilibrium, they are both zero.
- * Even with current flow, V_{neutral}^p and V_{neutral}^n remain negligibly small since a very small electric field is sufficient to create the required $J_p^{\text{drift}} = q\mu_p p \mathcal{E}$ or $J_n^{\text{drift}} = q\mu_n n \mathcal{E}$ (note that *p* and *n* in these equations represent the *majority* carrier densities).

Where does the voltage drop?





Where does the voltage drop?





- * V_j is the voltage across the junction and is equal to V_{bi} in equilibrium. We have shown, using Poisson's equation, that $V_j \propto W^2$ where W is the depletion width.

Where does the voltage drop?





- * V_j is the voltage across the junction and is equal to V_{bi} in equilibrium. We have shown, using Poisson's equation, that $V_j \propto W^2$ where W is the depletion width.
- * In equilibrium, $V_p = V_n$, and we get
 (1): $V_{\text{contact}}^p - V_{bi} + V_{\text{contact}}^n = 0$, taking voltage drop as positive.
 (We assume that the signs of V_{contact}^p and V_{contact}^n are taken into account.)

Where does the voltage drop?





- * V_j is the voltage across the junction and is equal to V_{bi} in equilibrium. We have shown, using Poisson's equation, that $V_j \propto W^2$ where W is the depletion width.
- * In equilibrium, $V_p = V_n$, and we get
 - (1): $V_{\text{contact}}^p - V_{bi} + V_{\text{contact}}^n = 0$, taking voltage drop as positive.
(We assume that the signs of V_{contact}^p and V_{contact}^n are taken into account.)
- * When a bias is applied, we have
 - (2): $V_{\text{contact}}^p - V_j + V_{\text{contact}}^n = V_p - V_n = V_a$.

Where does the voltage drop?





- * V_j is the voltage across the junction and is equal to V_{bi} in equilibrium. We have shown, using Poisson's equation, that $V_j \propto W^2$ where W is the depletion width.
- * In equilibrium, $V_p = V_n$, and we get
 (1): $V_{\text{contact}}^p - V_{bi} + V_{\text{contact}}^n = 0$, taking voltage drop as positive.
 (We assume that the signs of V_{contact}^p and V_{contact}^n are taken into account.)
- * When a bias is applied, we have
 (2): $V_{\text{contact}}^p - V_j + V_{\text{contact}}^n = V_p - V_n = V_a$.
- * (1) - (2) gives $-V_{bi} + V_j = -V_a$, i.e., $V_j = V_{bi} - V_a$

Example: forward bias



For an abrupt silicon pn junction, the built-in voltage is $V_{bi} = 0.85 \text{ V}$. Let W_0 and W_1 denote the depletion widths for $V_a = 0 \text{ V}$ and $V_a = 0.6 \text{ V}$, respectively. What is W_1/W_0 ?



Example: forward bias



For an abrupt silicon pn junction, the built-in voltage is $V_{bi} = 0.85 \text{ V}$. Let W_0 and W_1 denote the depletion widths for $V_a = 0 \text{ V}$ and $V_a = 0.6 \text{ V}$, respectively. What is W_1/W_0 ?

Solution: $V_j \propto W^2 \rightarrow V_j = kW^2$.

Example: forward bias





For an abrupt silicon pn junction, the built-in voltage is $V_{bi} = 0.85 \text{ V}$. Let W_0 and W_1 denote the depletion widths for $V_a = 0 \text{ V}$ and $V_a = 0.6 \text{ V}$, respectively. What is W_1/W_0 ?

Solution: $V_j \propto W^2 \rightarrow V_j = kW^2$.

$$V_{bi} = kW_0^2 \quad (\text{for } V_a = 0 \text{ V})$$

Example: forward bias





For an abrupt silicon pn junction, the built-in voltage is $V_{bi} = 0.85\text{ V}$. Let W_0 and W_1 denote the depletion widths for $V_a = 0\text{ V}$ and $V_a = 0.6\text{ V}$, respectively. What is W_1/W_0 ?

Solution: $V_j \propto W^2 \rightarrow V_j = kW^2$.

$$V_{bi} = kW_0^2 \quad (\text{for } V_a = 0\text{ V})$$

$$V_{bi} - 0.6\text{ V} = kW_1^2 \quad (\text{for } V_a = 0.6\text{ V})$$

Example: forward bias



For an abrupt silicon pn junction, the built-in voltage is $V_{bi} = 0.85 \text{ V}$. Let W_0 and W_1 denote the depletion widths for $V_a = 0 \text{ V}$ and $V_a = 0.6 \text{ V}$, respectively. What is W_1/W_0 ?



Solution: $V_j \propto W^2 \rightarrow V_j = kW^2$.

$$V_{bi} = kW_0^2 \quad (\text{for } V_a = 0 \text{ V})$$

$$V_{bi} - 0.6 \text{ V} = kW_1^2 \quad (\text{for } V_a = 0.6 \text{ V})$$

$$\rightarrow \frac{0.85 - 0.6}{0.85} = \left(\frac{W_1}{W_0} \right)^2 \rightarrow \frac{W_1}{W_0} = 0.54.$$

Example: forward bias



For an abrupt silicon pn junction, the built-in voltage is $V_{bi} = 0.85 \text{ V}$. Let W_0 and W_1 denote the depletion widths for $V_a = 0 \text{ V}$ and $V_a = 0.6 \text{ V}$, respectively. What is W_1/W_0 ?

Solution: $V_j \propto W^2 \rightarrow V_j = kW^2$.



$$V_{bi} = kW_0^2 \quad (\text{for } V_a = 0 \text{ V})$$

$$V_{bi} - 0.6 \text{ V} = kW_1^2 \quad (\text{for } V_a = 0.6 \text{ V})$$

$$\rightarrow \frac{0.85 - 0.6}{0.85} = \left(\frac{W_1}{W_0} \right)^2 \rightarrow \frac{W_1}{W_0} = 0.54.$$



Application of a forward bias of 0.6 V causes the depletion region to shrink by a factor 0.54 .

Example: reverse bias



For an abrupt silicon pn junction, the built-in voltage is $V_{bi} = 0.85 \text{ V}$. Let W_0 and W_1 denote the depletion widths for $V_a = 0 \text{ V}$ and $V_a = -2 \text{ V}$ (i.e., a reverse bias V_R of 2 V), respectively. What is W_1/W_0 ?



Example: reverse bias



For an abrupt silicon pn junction, the built-in voltage is $V_{bi} = 0.85$ V. Let W_0 and W_1 denote the depletion widths for $V_a = 0$ V and $V_a = -2$ V (i.e., a reverse bias V_R of 2 V), respectively. What is W_1/W_0 ?

Solution: $V_j \propto W^2 \rightarrow V_j = kW^2$.

Example: reverse bias





For an abrupt silicon pn junction, the built-in voltage is $V_{bi} = 0.85 \text{ V}$. Let W_0 and W_1 denote the depletion widths for $V_a = 0 \text{ V}$ and $V_a = -2 \text{ V}$ (i.e., a reverse bias V_R of 2 V), respectively. What is W_1/W_0 ?

Solution: $V_j \propto W^2 \rightarrow V_j = kW^2$.

$$V_{bi} = kW_0^2 \quad (\text{for } V_a = 0 \text{ V})$$

Example: reverse bias





For an abrupt silicon pn junction, the built-in voltage is $V_{bi} = 0.85 \text{ V}$. Let W_0 and W_1 denote the depletion widths for $V_a = 0 \text{ V}$ and $V_a = -2 \text{ V}$ (i.e., a reverse bias V_R of 2 V), respectively. What is W_1/W_0 ?

Solution: $V_j \propto W^2 \rightarrow V_j = kW^2$.

$$V_{bi} = kW_0^2 \quad (\text{for } V_a = 0 \text{ V})$$

$$V_{bi} - (-2) \text{ V} = kW_1^2 \quad (\text{for } V_a = -2 \text{ V})$$

Example: reverse bias



For an abrupt silicon *pn* junction, the built-in voltage is $V_{bi} = 0.85$ V. Let W_0 and W_1 denote the depletion widths for $V_a = 0$ V and $V_a = -2$ V (i.e., a reverse bias V_R of 2 V), respectively. What is W_1/W_0 ?



Solution: $V_j \propto W^2 \rightarrow V_j = kW^2$.

$$V_{bi} = kW_0^2 \quad (\text{for } V_a = 0 \text{ V})$$

$$V_{bi} - (-2) \text{ V} = kW_1^2 \quad (\text{for } V_a = -2 \text{ V})$$

$$\rightarrow \frac{0.85 + 2}{0.85} = \left(\frac{W_1}{W_0} \right)^2 \rightarrow \frac{W_1}{W_0} = 1.83.$$

Example: reverse bias



For an abrupt silicon pn junction, the built-in voltage is $V_{bi} = 0.85 \text{ V}$. Let W_0 and W_1 denote the depletion widths for $V_a = 0 \text{ V}$ and $V_a = -2 \text{ V}$ (i.e., a reverse bias V_R of 2 V), respectively. What is W_1/W_0 ?

Solution: $V_j \propto W^2 \rightarrow V_j = kW^2$.


$$V_{bi} = kW_0^2 \quad (\text{for } V_a = 0 \text{ V})$$

$$V_{bi} - (-2) \text{ V} = kW_1^2 \quad (\text{for } V_a = -2 \text{ V})$$

$$\rightarrow \frac{0.85 + 2}{0.85} = \left(\frac{W_1}{W_0} \right)^2 \rightarrow \frac{W_1}{W_0} = 1.83.$$


Application of a reverse bias of 2 V causes the depletion region to expand by a factor 1.83 .

Forward bias




Forward bias

- * The electrostatic conditions (viz., $\rho(x)$, $\mathcal{E}(x)$, $\psi(x)$) under forward bias are similar to the equilibrium situation except for a reduced junction voltage ($V_{bi} - V_a$).



Forward bias

- * The electrostatic conditions (viz., $\rho(x)$, $\mathcal{E}(x)$, $\psi(x)$) under forward bias are similar to the equilibrium situation except for a reduced junction voltage ($V_{bi} - V_a$).
- * The depletion width, the maximum electric field, and the junction voltage drop decrease with forward bias.




Forward bias


- * The electrostatic conditions (viz., $\rho(x)$, $\mathcal{E}(x)$, $\psi(x)$) under forward bias are similar to the equilibrium situation except for a reduced junction voltage ($V_{bi} - V_a$).
- * The depletion width, the maximum electric field, and the junction voltage drop decrease with forward bias.
- * Solving Poisson's equation using the depletion approximation, we get

$$W = \sqrt{\frac{2\epsilon}{q} \left(\frac{N_a + N_d}{N_a N_d} \right) (V_{bi} - V_a)},$$

$$W_n = \frac{N_a}{N_a + N_d} W, \quad W_p = \frac{N_d}{N_a + N_d} W.$$




Forward bias




Forward bias

- * Although the equilibrium condition is disturbed with an applied bias, the situation sufficiently far from the depletion region is hardly different.




Forward bias

- * Although the equilibrium condition is disturbed with an applied bias, the situation sufficiently far from the depletion region is hardly different.
- * We can extend the Fermi level concept to describe carrier concentrations sufficiently far from the depletion region.




Forward bias

- * Although the equilibrium condition is disturbed with an applied bias, the situation sufficiently far from the depletion region is hardly different.
- * We can extend the Fermi level concept to describe carrier concentrations sufficiently far from the depletion region.
- * $p = N_v e^{-(E_{Fp} - E_v)/kT}$ on the p -side,
 $n = N_c e^{-(E_c - E_{Fn})/kT}$ on the n -side.




Forward bias

- * Although the equilibrium condition is disturbed with an applied bias, the situation sufficiently far from the depletion region is hardly different.
- * We can extend the Fermi level concept to describe carrier concentrations sufficiently far from the depletion region.
- * $p = N_v e^{-(E_{Fp} - E_v)/kT}$ on the p -side,
 $n = N_c e^{-(E_c - E_{Fn})/kT}$ on the n -side.
- * The Fermi levels are called “quasi Fermi levels” since the situation is *almost* like equilibrium.



Forward bias

- Although the equilibrium condition is disturbed with an applied bias, the situation sufficiently far from the depletion region is hardly different.
- We can extend the Fermi level concept to describe carrier concentrations sufficiently far from the depletion region.
- $p = N_v e^{-(E_{Fp} - E_v)/kT}$ on the p -side,
 $n = N_c e^{-(E_c - E_{Fn})/kT}$ on the n -side.
- The Fermi levels are called “quasi Fermi levels” since the situation is *almost* like equilibrium.
- From the band diagram, we see that
 $E_g = \Delta_p + \Delta_n + qV_{bi}$,



Forward bias

- Although the equilibrium condition is disturbed with an applied bias, the situation sufficiently far from the depletion region is hardly different.
- We can extend the Fermi level concept to describe carrier concentrations sufficiently far from the depletion region.


- $p = N_v e^{-(E_{Fp} - E_v)/kT}$ on the p -side,
 $n = N_c e^{-(E_c - E_{Fn})/kT}$ on the n -side.

- The Fermi levels are called “quasi Fermi levels” since the situation is *almost* like equilibrium.

- From the band diagram, we see that

$$E_g = \Delta_p + \Delta_n + qV_{bi},$$

$$E_g = \Delta_p + (E_{Fn} - E_{Fp}) + \Delta_n + q(V_{bi} - V_a)$$



Forward bias

- Although the equilibrium condition is disturbed with an applied bias, the situation sufficiently far from the depletion region is hardly different.
- We can extend the Fermi level concept to describe carrier concentrations sufficiently far from the depletion region.

- $p = N_v e^{-(E_{Fp} - E_v)/kT}$ on the p -side,
 $n = N_c e^{-(E_c - E_{Fn})/kT}$ on the n -side.


- The Fermi levels are called “quasi Fermi levels” since the situation is *almost* like equilibrium.

- From the band diagram, we see that


$$E_g = \Delta_p + \Delta_n + qV_{bi},$$

$$E_g = \Delta_p + (E_{Fn} - E_{Fp}) + \Delta_n + q(V_{bi} - V_a)$$

$$\rightarrow E_{Fn} - E_{Fp} = qV_a.$$




Reverse bias




Reverse bias

- * The electrostatic conditions (viz., $\rho(x)$, $\mathcal{E}(x)$, $\psi(x)$) under reverse bias are similar to the equilibrium situation except for an increased junction voltage ($V_{bi} + V_R$).



Reverse bias

- * The electrostatic conditions (viz., $\rho(x)$, $\mathcal{E}(x)$, $\psi(x)$) under reverse bias are similar to the equilibrium situation except for an increased junction voltage ($V_{bi} + V_R$).
- * The depletion width, the maximum electric field, and the junction voltage drop increase with reverse bias.




Reverse bias


- * The electrostatic conditions (viz., $\rho(x)$, $\mathcal{E}(x)$, $\psi(x)$) under reverse bias are similar to the equilibrium situation except for an increased junction voltage ($V_{bi} + V_R$).
- * The depletion width, the maximum electric field, and the junction voltage drop increase with reverse bias.
- * Solving Poisson's equation using the depletion approximation, we get

$$W = \sqrt{\frac{2\epsilon}{q} \left(\frac{N_a + N_d}{N_a N_d} \right) (V_{bi} + V_R)},$$

$$W_n = \frac{N_a}{N_a + N_d} W, \quad W_p = \frac{N_d}{N_a + N_d} W.$$




Reverse bias




Reverse bias

- * Although the equilibrium condition is disturbed with an applied bias, the situation sufficiently far from the depletion region is hardly different.




Reverse bias

- * Although the equilibrium condition is disturbed with an applied bias, the situation sufficiently far from the depletion region is hardly different.
- * We can extend the Fermi level concept to describe carrier concentrations sufficiently far from the depletion region.




Reverse bias

- * Although the equilibrium condition is disturbed with an applied bias, the situation sufficiently far from the depletion region is hardly different.
- * We can extend the Fermi level concept to describe carrier concentrations sufficiently far from the depletion region.
- * $p = N_v e^{-(E_{Fp} - E_v)/kT}$ on the p -side,
 $n = N_c e^{-(E_c - E_{Fn})/kT}$ on the n -side.




Reverse bias

- Although the equilibrium condition is disturbed with an applied bias, the situation sufficiently far from the depletion region is hardly different.
- We can extend the Fermi level concept to describe carrier concentrations sufficiently far from the depletion region.
- $p = N_v e^{-(E_{Fp} - E_v)/kT}$ on the p -side,
 $n = N_c e^{-(E_c - E_{Fn})/kT}$ on the n -side.
- The Fermi levels are called “quasi Fermi levels” since the situation is *almost* like equilibrium.



Reverse bias

- Although the equilibrium condition is disturbed with an applied bias, the situation sufficiently far from the depletion region is hardly different.
- We can extend the Fermi level concept to describe carrier concentrations sufficiently far from the depletion region.
- $p = N_v e^{-(E_{Fp} - E_v)/kT}$ on the p -side,
 $n = N_c e^{-(E_c - E_{Fn})/kT}$ on the n -side.
- The Fermi levels are called “quasi Fermi levels” since the situation is *almost* like equilibrium.
- From the band diagram, we see that
 $E_g = \Delta_p + \Delta_n + qV_{bi}$,



Reverse bias

- * Although the equilibrium condition is disturbed with an applied bias, the situation sufficiently far from the depletion region is hardly different.

- * We can extend the Fermi level concept to describe carrier concentrations sufficiently far from the depletion region.


- * $p = N_v e^{-(E_{Fp} - E_v)/kT}$ on the p -side,
 $n = N_c e^{-(E_c - E_{Fn})/kT}$ on the n -side.

- * The Fermi levels are called “quasi Fermi levels” since the situation is *almost* like equilibrium.

- * From the band diagram, we see that

$$E_g = \Delta_p + \Delta_n + qV_{bi},$$

$$E_g = \Delta_p - (E_{Fp} - E_{Fn}) + \Delta_n + q(V_{bi} + V_R)$$



Reverse bias

- * Although the equilibrium condition is disturbed with an applied bias, the situation sufficiently far from the depletion region is hardly different.

- * We can extend the Fermi level concept to describe carrier concentrations sufficiently far from the depletion region.

- * $p = N_v e^{-(E_{Fp} - E_v)/kT}$ on the p -side,
 $n = N_c e^{-(E_c - E_{Fn})/kT}$ on the n -side.


- * The Fermi levels are called “quasi Fermi levels” since the situation is *almost* like equilibrium.

- * From the band diagram, we see that


$$E_g = \Delta_p + \Delta_n + qV_{bi},$$

$$E_g = \Delta_p - (E_{Fp} - E_{Fn}) + \Delta_n + q(V_{bi} + V_R)$$



$$\rightarrow E_{Fp} - E_{Fn} = qV_R.$$



Current densities in forward bias




$N_d = 2 \times 10^{17} \text{ cm}^{-3}$	$\tau_n = 1 \text{ ns}$
$N_a = 10^{17} \text{ cm}^{-3}$	$\tau_p = 1 \text{ ns}$
$\mu_n = 1400 \text{ cm}^2/\text{V-s}$	$T = 300 \text{ K}$
$\mu_p = 500 \text{ cm}^2/\text{V-s}$	$V_a = 0.6 \text{ V}$





Near the junction,

Current densities in forward bias




$N_d = 2 \times 10^{17} \text{ cm}^{-3}$	$\tau_n = 1 \text{ ns}$
$N_a = 10^{17} \text{ cm}^{-3}$	$\tau_p = 1 \text{ ns}$
$\mu_n = 1400 \text{ cm}^2/\text{V-s}$	$T = 300 \text{ K}$
$\mu_p = 500 \text{ cm}^2/\text{V-s}$	$V_a = 0.6 \text{ V}$





Near the junction,

* Although the equilibrium condition is disturbed, we still have $J_p^{\text{diff}} \approx -J_p^{\text{drift}}$, and $J_n^{\text{diff}} \approx -J_n^{\text{drift}}$.

Current densities in forward bias




$N_d = 2 \times 10^{17} \text{ cm}^{-3}$	$\tau_n = 1 \text{ ns}$
$N_a = 10^{17} \text{ cm}^{-3}$	$\tau_p = 1 \text{ ns}$
$\mu_n = 1400 \text{ cm}^2/\text{V-s}$	$T = 300 \text{ K}$
$\mu_p = 500 \text{ cm}^2/\text{V-s}$	$V_a = 0.6 \text{ V}$



Near the junction,


- * Although the equilibrium condition is disturbed, we still have $J_p^{\text{diff}} \approx -J_p^{\text{drift}}$, and $J_n^{\text{diff}} \approx -J_n^{\text{drift}}$.
- * The net current densities J_n and J_p are much smaller than the drift and diffusion components.

Current densities in reverse bias




$N_d = 2 \times 10^{17} \text{ cm}^{-3}$	$\tau_n = 1 \text{ ns}$
$N_a = 10^{17} \text{ cm}^{-3}$	$\tau_p = 1 \text{ ns}$
$\mu_n = 1400 \text{ cm}^2/\text{V-s}$	$T = 300 \text{ K}$
$\mu_p = 500 \text{ cm}^2/\text{V-s}$	$V_a = -1 \text{ V}$



Near the junction,



Current densities in reverse bias




$N_d = 2 \times 10^{17} \text{ cm}^{-3}$	$\tau_n = 1 \text{ ns}$
$N_a = 10^{17} \text{ cm}^{-3}$	$\tau_p = 1 \text{ ns}$
$\mu_n = 1400 \text{ cm}^2/\text{V-s}$	$T = 300 \text{ K}$
$\mu_p = 500 \text{ cm}^2/\text{V-s}$	$V_a = -1 \text{ V}$





Near the junction,

* Although the equilibrium condition is disturbed, we still have $J_p^{\text{diff}} \approx -J_p^{\text{drift}}$, and $J_n^{\text{diff}} \approx -J_n^{\text{drift}}$.

Current densities in reverse bias




$N_d = 2 \times 10^{17} \text{ cm}^{-3}$	$\tau_n = 1 \text{ ns}$
$N_a = 10^{17} \text{ cm}^{-3}$	$\tau_p = 1 \text{ ns}$
$\mu_n = 1400 \text{ cm}^2/\text{V-s}$	$T = 300 \text{ K}$
$\mu_p = 500 \text{ cm}^2/\text{V-s}$	$V_a = -1 \text{ V}$




Near the junction,

- * Although the equilibrium condition is disturbed, we still have $J_p^{\text{diff}} \approx -J_p^{\text{drift}}$, and $J_n^{\text{diff}} \approx -J_n^{\text{drift}}$.
- * The net current densities J_n and J_p are much smaller than the drift and diffusion components.

Current densities in reverse bias



$N_d = 2 \times 10^{17} \text{ cm}^{-3}$	$\tau_n = 1 \text{ ns}$
$N_a = 10^{17} \text{ cm}^{-3}$	$\tau_p = 1 \text{ ns}$
$\mu_n = 1400 \text{ cm}^2/\text{V-s}$	$T = 300 \text{ K}$
$\mu_p = 500 \text{ cm}^2/\text{V-s}$	$V_a = -1 \text{ V}$




Near the junction,

- * Although the equilibrium condition is disturbed, we still have $J_p^{\text{diff}} \approx -J_p^{\text{drift}}$, and $J_n^{\text{diff}} \approx -J_n^{\text{drift}}$.
- * The net current densities J_n and J_p are much smaller than the drift and diffusion components.
- * Note that J_{total} in reverse bias is negligibly small compared to the forward bias case (0.7 A/cm^2 for $V_a = 0.6 \text{ V}$). For all practical purposes, we can say that the current is zero for reverse bias.

pn junction: derivation of *I*-*V* equation


Definitions:



pn junction: derivation of I - V equation

Definitions:

p_{p0} : equilibrium hole density in the neutral p -region




pn junction: derivation of I - V equation

Definitions:

p_{p0} : equilibrium hole density in the neutral p -region

p_{n0} : equilibrium hole density in the neutral n -region




pn junction: derivation of I - V equation

Definitions:

p_{p0} : equilibrium hole density in the neutral p -region

p_{n0} : equilibrium hole density in the neutral n -region

n_{p0} : equilibrium electron density in the neutral p -region



pn junction: derivation of I - V equation


Definitions:

p_{p0} : equilibrium hole density in the neutral p -region

p_{n0} : equilibrium hole density in the neutral n -region

n_{p0} : equilibrium electron density in the neutral p -region

n_{n0} : equilibrium electron density in the neutral n -region



pn junction: derivation of I - V equation

Definitions:


p_{p0} : equilibrium hole density in the neutral p -region

p_{n0} : equilibrium hole density in the neutral n -region

n_{p0} : equilibrium electron density in the neutral p -region

n_{n0} : equilibrium electron density in the neutral n -region

p_{p0} and n_{n0} are majority carrier densities.



pn junction: derivation of I - V equation

Definitions:

p_{p0} : equilibrium hole density in the neutral p -region


p_{n0} : equilibrium hole density in the neutral n -region

n_{p0} : equilibrium electron density in the neutral p -region

n_{n0} : equilibrium electron density in the neutral n -region

p_{p0} and n_{n0} are majority carrier densities.

p_{n0} and n_{p0} are minority carrier densities.



pn junction: derivation of I - V equation

Definitions:

p_{p0} : equilibrium hole density in the neutral p -region

p_{n0} : equilibrium hole density in the neutral n -region


n_{p0} : equilibrium electron density in the neutral p -region

n_{n0} : equilibrium electron density in the neutral n -region

p_{p0} and n_{n0} are majority carrier densities.

p_{n0} and n_{p0} are minority carrier densities.

Example: $N_a = 5 \times 10^{16} \text{ cm}^{-3}$, $N_d = 10^{18} \text{ cm}^{-3}$ ($T = 300 \text{ K}$).



pn junction: derivation of I - V equation

Definitions:

p_{p0} : equilibrium hole density in the neutral p -region

p_{n0} : equilibrium hole density in the neutral n -region

n_{p0} : equilibrium electron density in the neutral p -region


n_{n0} : equilibrium electron density in the neutral n -region

p_{p0} and n_{n0} are majority carrier densities.

p_{n0} and n_{p0} are minority carrier densities.

Example: $N_a = 5 \times 10^{16} \text{ cm}^{-3}$, $N_d = 10^{18} \text{ cm}^{-3}$ ($T = 300 \text{ K}$).

$\rightarrow p_{p0} \approx N_a = 5 \times 10^{16} \text{ cm}^{-3}$,



pn junction: derivation of I - V equation

Definitions:

p_{p0} : equilibrium hole density in the neutral p -region

p_{n0} : equilibrium hole density in the neutral n -region

n_{p0} : equilibrium electron density in the neutral p -region

n_{n0} : equilibrium electron density in the neutral n -region


p_{p0} and n_{n0} are majority carrier densities.

p_{n0} and n_{p0} are minority carrier densities.

Example: $N_a = 5 \times 10^{16} \text{ cm}^{-3}$, $N_d = 10^{18} \text{ cm}^{-3}$ ($T = 300 \text{ K}$).

$\rightarrow p_{p0} \approx N_a = 5 \times 10^{16} \text{ cm}^{-3}$,

$n_{n0} \approx N_d = 10^{18} \text{ cm}^{-3}$,



pn junction: derivation of *I*-*V* equation

Definitions:

p_{p0} : equilibrium hole density in the neutral *p*-region

p_{n0} : equilibrium hole density in the neutral *n*-region

n_{p0} : equilibrium electron density in the neutral *p*-region

n_{n0} : equilibrium electron density in the neutral *n*-region

p_{p0} and n_{n0} are majority carrier densities.


p_{n0} and n_{p0} are minority carrier densities.

Example: $N_a = 5 \times 10^{16} \text{ cm}^{-3}$, $N_d = 10^{18} \text{ cm}^{-3}$ ($T = 300 \text{ K}$).

$$\rightarrow p_{p0} \approx N_a = 5 \times 10^{16} \text{ cm}^{-3},$$

$$n_{n0} \approx N_d = 10^{18} \text{ cm}^{-3},$$

$$n_{p0} = \frac{n_i^2}{p_{p0}} = \frac{(1.5 \times 10^{10})^2}{5 \times 10^{16}} = 4.5 \times 10^3 \text{ cm}^{-3},$$



pn junction: derivation of I - V equation

Definitions:

p_{p0} : equilibrium hole density in the neutral p -region

p_{n0} : equilibrium hole density in the neutral n -region

n_{p0} : equilibrium electron density in the neutral p -region

n_{n0} : equilibrium electron density in the neutral n -region

p_{p0} and n_{n0} are majority carrier densities.

p_{n0} and n_{p0} are minority carrier densities.


Example: $N_a = 5 \times 10^{16} \text{ cm}^{-3}$, $N_d = 10^{18} \text{ cm}^{-3}$ ($T = 300 \text{ K}$).

$$\rightarrow p_{p0} \approx N_a = 5 \times 10^{16} \text{ cm}^{-3},$$


$$n_{n0} \approx N_d = 10^{18} \text{ cm}^{-3},$$

$$n_{p0} = \frac{n_i^2}{p_{p0}} = \frac{(1.5 \times 10^{10})^2}{5 \times 10^{16}} = 4.5 \times 10^3 \text{ cm}^{-3},$$


$$p_{n0} = \frac{n_i^2}{n_{n0}} = \frac{(1.5 \times 10^{10})^2}{10^{18}} = 2.25 \times 10^2 \text{ cm}^{-3}.$$



pn junction: derivation of I - V equation




pn junction: derivation of I - V equation




* Since $V_j = V_{bi} - V_a$ and $W \propto \sqrt{V_j}$, the depletion region is narrower under forward bias, wider under reverse bias.

pn junction: derivation of I - V equation




- * Since $V_j = V_{bi} - V_a$ and $W \propto \sqrt{V_j}$, the depletion region is narrower under forward bias, wider under reverse bias.
- * Equilibrium concentrations (note: log scale for n and p):
 $p = p_{p0}$, $n = n_{p0}$ in the neutral p -region.

pn junction: derivation of I - V equation




- * Since $V_j = V_{bi} - V_a$ and $W \propto \sqrt{V_j}$, the depletion region is narrower under forward bias, wider under reverse bias.
- * Equilibrium concentrations (note: log scale for n and p):
 - $p = p_{p0}$, $n = n_{p0}$ in the neutral p -region.
 - $n = n_{n0}$, $p = p_{n0}$ in the neutral n -region.

pn junction: derivation of I - V equation




$$J_p^{\text{diff}} \approx -J_p^{\text{drift}}$$

pn junction: derivation of I - V equation




$$J_p^{\text{diff}} \approx -J_p^{\text{drift}} \rightarrow q \mu_p p \mathcal{E} = q D_p \frac{dp}{dx},$$

pn junction: derivation of I - V equation



$$J_p^{\text{diff}} \approx -J_p^{\text{drift}} \rightarrow q \mu_p p \mathcal{E} = q D_p \frac{dp}{dx}, \text{ i.e., } \mathcal{E} = -\frac{d\psi}{dx} = \frac{D_p}{\mu_p} \frac{1}{p} \frac{dp}{dx}.$$


pn junction: derivation of I - V equation



$$J_p^{\text{diff}} \approx -J_p^{\text{drift}} \rightarrow q \mu_p p \mathcal{E} = q D_p \frac{dp}{dx}, \text{ i.e., } \mathcal{E} = -\frac{d\psi}{dx} = \frac{D_p}{\mu_p} \frac{1}{p} \frac{dp}{dx}.$$

$$\frac{D}{\mu} = \frac{kT}{q} \rightarrow \int d\psi = -V_T \int \frac{1}{p} dp$$


pn junction: derivation of I - V equation



$$J_p^{\text{diff}} \approx -J_p^{\text{drift}} \rightarrow q \mu_p p \mathcal{E} = q D_p \frac{dp}{dx}, \text{ i.e., } \mathcal{E} = -\frac{d\psi}{dx} = \frac{D_p}{\mu_p} \frac{1}{p} \frac{dp}{dx}.$$

$$\frac{D}{\mu} = \frac{kT}{q} \rightarrow \int d\psi = -V_T \int \frac{1}{p} dp \rightarrow \psi \Big|_{x_1}^{x_2} = -V_T \log \frac{p(x_2)}{p(x_1)}$$


pn junction: derivation of I - V equation



$$J_p^{\text{diff}} \approx -J_p^{\text{drift}} \rightarrow q \mu_p p \mathcal{E} = q D_p \frac{dp}{dx}, \text{ i.e., } \mathcal{E} = -\frac{d\psi}{dx} = \frac{D_p}{\mu_p} \frac{1}{p} \frac{dp}{dx}.$$


$$\frac{D}{\mu} = \frac{kT}{q} \rightarrow \int d\psi = -V_T \int \frac{1}{p} dp \rightarrow \psi \Big|_{x_1}^{x_2} = -V_T \log \frac{p(x_2)}{p(x_1)} \rightarrow \frac{p(x_n)}{p(x_p)} = \exp \left(\frac{\psi(x_p) - \psi(x_n)}{V_T} \right).$$

pn junction: derivation of I - V equation



$$J_p^{\text{diff}} \approx -J_p^{\text{drift}} \rightarrow \frac{p(x_n)}{p(x_p)} = \exp\left(\frac{\psi(x_p) - \psi(x_n)}{V_T}\right).$$


pn junction: derivation of I - V equation




$$J_p^{\text{diff}} \approx -J_p^{\text{drift}} \rightarrow \frac{p(x_n)}{p(x_p)} = \exp\left(\frac{\psi(x_p) - \psi(x_n)}{V_T}\right).$$

$$J_n^{\text{diff}} \approx -J_n^{\text{drift}} \rightarrow \frac{n(x_n)}{n(x_p)} = \exp\left(\frac{\psi(x_n) - \psi(x_p)}{V_T}\right).$$

pn junction: derivation of I - V equation




pn junction: derivation of I - V equation




* When a bias is applied, the minority carrier concentrations in the neutral regions can change substantially.

pn junction: derivation of I - V equation





- * When a bias is applied, the minority carrier concentrations in the neutral regions can change substantially.
- * There is a corresponding change in the majority carrier concentrations as well, and it serves to keep these regions charge-neutral.

pn junction: derivation of I - V equation




- * When a bias is applied, the minority carrier concentrations in the neutral regions can change substantially.
- * There is a corresponding change in the majority carrier concentrations as well, and it serves to keep these regions charge-neutral.
- * Low-level injection: $\Delta n \approx \Delta p \ll p_{p0}$ in the neutral p -region $\rightarrow p(x) \approx p_{p0}$ for $x \leq x_p$
 $\Delta p \approx \Delta n \ll n_{n0}$ in the neutral n -region $\rightarrow n(x) \approx n_{n0}$ for $x \geq x_n$






$$* \frac{p(x_n)}{p(x_p)} = \exp\left(\frac{\psi(x_p) - \psi(x_n)}{V_T}\right), \quad \frac{n(x_n)}{n(x_p)} = \exp\left(\frac{\psi(x_n) - \psi(x_p)}{V_T}\right). \text{ Also, } \psi(x_n) - \psi(x_p) = V_j.$$



$$* \frac{p(x_n)}{p(x_p)} = \exp\left(\frac{\psi(x_p) - \psi(x_n)}{V_T}\right), \quad \frac{n(x_n)}{n(x_p)} = \exp\left(\frac{\psi(x_n) - \psi(x_p)}{V_T}\right). \text{ Also, } \psi(x_n) - \psi(x_p) = V_j.$$


* Low-level injection: $p(x) \approx p_{p0}$ for $x \leq x_p$, and $n(x) \approx n_{n0}$ for $x \geq x_n$.



$$* \frac{p(x_n)}{p(x_p)} = \exp\left(\frac{\psi(x_p) - \psi(x_n)}{V_T}\right), \quad \frac{n(x_n)}{n(x_p)} = \exp\left(\frac{\psi(x_n) - \psi(x_p)}{V_T}\right). \text{ Also, } \psi(x_n) - \psi(x_p) = V_j.$$

* Low-level injection: $p(x) \approx p_{p0}$ for $x \leq x_p$, and $n(x) \approx n_{n0}$ for $x \geq x_n$.

$$\rightarrow \frac{p(x_n)}{p_{p0}} = e^{-V_j/V_T} \rightarrow p(x_n) = p_{p0} e^{-V_j/V_T}$$




$$* \frac{p(x_n)}{p(x_p)} = \exp\left(\frac{\psi(x_p) - \psi(x_n)}{V_T}\right), \quad \frac{n(x_n)}{n(x_p)} = \exp\left(\frac{\psi(x_n) - \psi(x_p)}{V_T}\right). \text{ Also, } \psi(x_n) - \psi(x_p) = V_j.$$

* Low-level injection: $p(x) \approx p_{p0}$ for $x \leq x_p$, and $n(x) \approx n_{n0}$ for $x \geq x_n$.

$$\rightarrow \frac{p(x_n)}{p_{p0}} = e^{-V_j/V_T} \rightarrow p(x_n) = p_{p0} e^{-V_j/V_T}$$


$$\frac{n_{n0}}{n(x_p)} = e^{V_j/V_T} \rightarrow n(x_p) = n_{n0} e^{-V_j/V_T}.$$



$$p(x_n) = p_{p0} e^{-V_j/V_T}$$

$$n(x_p) = n_{n0} e^{-V_j/V_T}$$

$$V_j = V_{bi} - V_a$$




$$p(x_n) = p_{p0} e^{-V_j/V_T}$$

$$n(x_p) = n_{n0} e^{-V_j/V_T}$$

$$V_j = V_{bi} - V_a$$

$$\text{Equilibrium: } p(x_n) = p_{n0} = p_{p0} \exp\left(\frac{-V_{bi}}{V_T}\right), \quad n(x_p) = n_{p0} = n_{n0} \exp\left(\frac{-V_{bi}}{V_T}\right).$$




$$p(x_n) = p_{p0} e^{-V_j/V_T}$$

$$n(x_p) = n_{n0} e^{-V_j/V_T}$$

$$V_j = V_{bi} - V_a$$

$$\text{Equilibrium: } p(x_n) = p_{n0} = p_{p0} \exp\left(\frac{-V_{bi}}{V_T}\right), \quad n(x_p) = n_{p0} = n_{n0} \exp\left(\frac{-V_{bi}}{V_T}\right).$$

$$\text{With bias: } p(x_n) = p_{p0} \exp\left(\frac{-V_{bi} + V_a}{V_T}\right), \quad n(x_p) = n_{n0} \exp\left(\frac{-V_{bi} + V_a}{V_T}\right).$$



$$p(x_n) = p_{p0} e^{-V_j/V_T}$$


$$n(x_p) = n_{n0} e^{-V_j/V_T}$$

$$V_j = V_{bi} - V_a$$

$$\text{Equilibrium: } p(x_n) = p_{n0} = p_{p0} \exp\left(\frac{-V_{bi}}{V_T}\right), \quad n(x_p) = n_{p0} = n_{n0} \exp\left(\frac{-V_{bi}}{V_T}\right).$$


$$\text{With bias: } p(x_n) = p_{p0} \exp\left(\frac{-V_{bi} + V_a}{V_T}\right), \quad n(x_p) = n_{n0} \exp\left(\frac{-V_{bi} + V_a}{V_T}\right).$$

$$p(x_n) = p_{n0} \exp\left(\frac{V_a}{V_T}\right), \quad n(x_p) = n_{p0} \exp\left(\frac{V_a}{V_T}\right).$$




Example: Consider an abrupt, uniformly doped silicon pn junction at $T = 300\text{ K}$, with $N_a = 5 \times 10^{16}\text{ cm}^{-3}$ and $N_d = 10^{18}\text{ cm}^{-3}$. Compute the depletion width and the minority carrier densities at the depletion region edges (x_p and x_n) for an applied bias of $+0.3\text{ V}$, $+0.6\text{ V}$, -1 V , -5 V .

($n_i = 1.5 \times 10^{10}\text{ cm}^{-3}$ for silicon at $T = 300\text{ K}$.)




Solution: $p_{p0} \approx N_a = 5 \times 10^{16} \text{ cm}^{-3} \rightarrow n_{p0} = \frac{n_i^2}{p_{p0}} = \frac{(1.5 \times 10^{10})^2}{5 \times 10^{16}} = 4.5 \times 10^3 \text{ cm}^{-3}.$



Solution: $p_{p0} \approx N_a = 5 \times 10^{16} \text{ cm}^{-3} \rightarrow n_{p0} = \frac{n_i^2}{p_{p0}} = \frac{(1.5 \times 10^{10})^2}{5 \times 10^{16}} = 4.5 \times 10^3 \text{ cm}^{-3}.$




$n_{n0} \approx N_d = 1 \times 10^{18} \text{ cm}^{-3} \rightarrow p_{n0} = \frac{n_i^2}{n_{n0}} = \frac{(1.5 \times 10^{10})^2}{1 \times 10^{18}} = 2.25 \times 10^2 \text{ cm}^{-3}.$




Solution: $p_{p0} \approx N_a = 5 \times 10^{16} \text{ cm}^{-3} \rightarrow n_{p0} = \frac{n_i^2}{p_{p0}} = \frac{(1.5 \times 10^{10})^2}{5 \times 10^{16}} = 4.5 \times 10^3 \text{ cm}^{-3}.$


$n_{n0} \approx N_d = 1 \times 10^{18} \text{ cm}^{-3} \rightarrow p_{n0} = \frac{n_i^2}{n_{n0}} = \frac{(1.5 \times 10^{10})^2}{1 \times 10^{18}} = 2.25 \times 10^2 \text{ cm}^{-3}.$

$V_{bi} = V_T \log \left(\frac{N_a N_d}{n_i^2} \right) = (0.0259 \text{ V}) \log \left(\frac{5 \times 10^{16} \times 10^{18}}{(1.5 \times 10^{10})^2} \right) = 0.86 \text{ V}.$






$$V_a = 0.3 \text{ V: } W = \sqrt{\frac{2\epsilon}{q} \frac{N_a + N_d}{N_a N_d} (V_{bi} - V_a)} = 0.12 \mu\text{m}.$$



$$V_a = 0.3 \text{ V: } W = \sqrt{\frac{2\epsilon}{q} \frac{N_a + N_d}{N_a N_d} (V_{bi} - V_a)} = 0.12 \mu\text{m}.$$




$$n(x_p) = n_{p0} \exp\left(\frac{V_a}{V_T}\right) = 4.5 \times 10^3 \times \exp\left(\frac{0.3}{0.0259}\right) = 4.83 \times 10^8 \text{ cm}^{-3}.$$




$$V_a = 0.3 \text{ V: } W = \sqrt{\frac{2\epsilon}{q} \frac{N_a + N_d}{N_a N_d} (V_{bi} - V_a)} = 0.12 \mu\text{m}.$$

$$n(x_p) = n_{p0} \exp\left(\frac{V_a}{V_T}\right) = 4.5 \times 10^3 \times \exp\left(\frac{0.3}{0.0259}\right) = 4.83 \times 10^8 \text{ cm}^{-3}.$$

$$p(x_n) = p_{n0} \exp\left(\frac{V_a}{V_T}\right) = 2.25 \times 10^2 \times \exp\left(\frac{0.3}{0.0259}\right) = 2.41 \times 10^7 \text{ cm}^{-3}.$$




V_a (V)	W (μm)	\mathcal{E}_m (kV/cm)	$n(x_p)$ (cm^{-3})	$p(x_n)$ (cm^{-3})
0.6	0.08	61.3	5.18×10^{13}	2.59×10^{12}
0.3	0.12	90.4	4.83×10^8	2.41×10^7
0.0	0.15	112.2	4.50×10^3	2.25×10^2
-1.0	0.22	165.3	$7.68 \times 10^{-14} \approx 0$	$3.84 \times 10^{-15} \approx 0$
-5.0	0.40	293.6	≈ 0	≈ 0




V_a (V)	W (μm)	\mathcal{E}_m (kV/cm)	$n(x_p)$ (cm^{-3})	$p(x_n)$ (cm^{-3})
0.6	0.08	61.3	5.18×10^{13}	2.59×10^{12}
0.3	0.12	90.4	4.83×10^8	2.41×10^7
0.0	0.15	112.2	4.50×10^3	2.25×10^2
-1.0	0.22	165.3	$7.68 \times 10^{-14} \approx 0$	$3.84 \times 10^{-15} \approx 0$
-5.0	0.40	293.6	≈ 0	≈ 0


* With forward bias, the minority carrier concentrations can increase by several orders of magnitude.



Equilibrium



Forward bias



Reverse bias

V_a (V)	W (μm)	\mathcal{E}_m (kV/cm)	$n(x_p)$ (cm^{-3})	$p(x_n)$ (cm^{-3})
0.6	0.08	61.3	5.18×10^{13}	2.59×10^{12}
0.3	0.12	90.4	4.83×10^8	2.41×10^7
0.0	0.15	112.2	4.50×10^3	2.25×10^2
-1.0	0.22	165.3	$7.68 \times 10^{-14} \approx 0$	$3.84 \times 10^{-15} \approx 0$
-5.0	0.40	293.6	≈ 0	≈ 0

- * With forward bias, the minority carrier concentrations can increase by several orders of magnitude.
- * With reverse bias, the minority carrier concentrations become very small and can be replaced with zero for all practical purposes.