# Symbol Detection in CDMA-OFDM Coexistence

 G V V Sharma
 06407010

 Aswani Kumar Ravi
 06307R13

 Nagraj T
 06307040

Department of Electrical Engineering IIT Bombay http://www.ee.iitb.ac.in/student/ aswanikumar/

向下 イヨト イヨト

э

One user transmits the symbol b using CDMA (spreading code). Another user transmits vector c using OFDM. Both use the same channel (carrier frequency).

(E) < E)</p>

- One user transmits the symbol b using CDMA (spreading code). Another user transmits vector c using OFDM. Both use the same channel (carrier frequency).
- OFDM demodulator output, assuming that the noise is AWGN

$$\mathbf{y} = b\mathbf{r} + \mathbf{c} + \sigma \mathbf{n}$$

where **n** is complex circularly Gaussian,  $\sigma^2$  the noise variance.

- One user transmits the symbol b using CDMA (spreading code). Another user transmits vector c using OFDM. Both use the same channel (carrier frequency).
- OFDM demodulator output, assuming that the noise is AWGN

$$\mathbf{y} = b\mathbf{r} + \mathbf{c} + \sigma \mathbf{n}$$

where **n** is complex circularly Gaussian,  $\sigma^2$  the noise variance.

A minimum power distortionless response (MPDR) approach
 [1] has been used in [2] for symbol detection in the above model.

通 とう きょう うちょう

- One user transmits the symbol b using CDMA (spreading code). Another user transmits vector c using OFDM. Both use the same channel (carrier frequency).
- OFDM demodulator output, assuming that the noise is AWGN

$$\mathbf{y} = b\mathbf{r} + \mathbf{c} + \sigma \mathbf{n}$$

where **n** is complex circularly Gaussian,  $\sigma^2$  the noise variance.

- A minimum power distortionless response (MPDR) approach
   [1] has been used in [2] for symbol detection in the above model.
- The Gaussian character of the noise was not exploited in the earlier method.

- One user transmits the symbol b using CDMA (spreading code). Another user transmits vector c using OFDM. Both use the same channel (carrier frequency).
- OFDM demodulator output, assuming that the noise is AWGN

$$\mathbf{y} = b\mathbf{r} + \mathbf{c} + \sigma \mathbf{n}$$

where **n** is complex circularly Gaussian,  $\sigma^2$  the noise variance.

- A minimum power distortionless response (MPDR) approach
   [1] has been used in [2] for symbol detection in the above model.
- The Gaussian character of the noise was not exploited in the earlier method.
- We wish to exploit this characteristic and use adaptive techniques for symbol detection.

(4月) (1日) (日)



H. L. Van Trees, Optimum Array Processing, John Wiley and Sons, NY 2002.

G. V. V. Sharma and S. H. Srinivasan, "Symbol Detection in CDMA-OFDM Coexistence," *IEEE PIMRC*, 2005.

イロト イヨト イヨト イヨト

3