

Monero Ring Signatures

Saravanan Vijayakumaran
sarva@ee.iitb.ac.in

Department of Electrical Engineering
Indian Institute of Technology Bombay

October 12, 2018

Monero Ring Signatures

- Transaction outputs store coins in one-time addresses
- Spending from a one-time address done via a ring signature over many one-time addresses
 - Spender chooses random one-time addresses from the blockchain
 - Creates a ring signature with the one-time address private key
 - Observers know that coins in one of the addresses were spent
- To prevent double spending, **linkable** ring signatures needed
 - Two linkable ring signatures created using same private key can be identified

Linkable Spontaneous Anonymous Group Signatures

- Consider an elliptic curve group E with cardinality L and base point G
- Let $x_i \in \mathbb{Z}_L^*$, $i = 0, 1, \dots, n-1$ be private keys with public keys $P_i = x_i G$
- Suppose a signer knows only x_j and not any of x_i for $i \neq j$
- The **key image** corresponding to P_j is $I = x_j H_p(P_j)$
- For a given message m , the signer generates the LSAG signature as follows:
 1. Picks $\alpha, s_i, i \neq j$ randomly from \mathbb{Z}_L
 2. Computes $L_j = \alpha G$, $R_j = \alpha H_p(P_j)$, and $c_{j+1} = H_s(m, L_j, R_j)$
 3. Increasing j modulo n , computes

$$L_{j+1} = s_{j+1} G + c_{j+1} P_{j+1}$$

$$R_{j+1} = s_{j+1} H_p(P_{j+1}) + c_{j+1} I$$

$$c_{j+2} = H_s(m, L_{j+1}, R_{j+1})$$

⋮

$$L_{j-1} = s_{j-1} G + c_{j-1} P_{j-1}$$

$$R_{j-1} = s_{j-1} H_p(P_{j-1}) + c_{j-1} I$$

$$c_j = H_s(m, L_{j-1}, R_{j-1})$$

4. Computes $s_j = \alpha - c_j x_j \implies L_j = s_j G + c_j P_j, R_j = s_j H_p(P_j) + c_j I$
 5. The ring signature is $\sigma = (I, c_0, s_0, s_1, \dots, s_{n-1})$
- Verifier computes L_j, R_j , remaining c_j 's, and checks that $H_s(m, L_{n-1}, R_{n-1}) = c_0$
 - Signatures with duplicate key images I will be rejected

LSAG Structure

- Rationale for choice of key image $I = x_j H_\rho(P_j)$
 - By collision resistance of H_ρ , I is unique for a given P_j
 - I does not reveal P_j as x_j is unknown to observers
 - Discrete log of $H_\rho(P_j)$ is unknown
- Comparison with regular ring signature calculation

$$\begin{array}{ll} L_{j+1} = s_{j+1}G + c_{j+1}P_{j+1} & L_{j+1} = s_{j+1}G + c_{j+1}P_{j+1} \\ R_{j+1} = s_{j+1}H_\rho(P_{j+1}) + c_{j+1}I & \\ c_{j+2} = H_s(m, L_{j+1}, R_{j+1}) & c_{j+2} = H_s(m, L_{j+1}) \\ \vdots & \vdots \\ L_{j-1} = s_{j-1}G + c_{j-1}P_{j-1} & L_{j-1} = s_{j-1}G + c_{j-1}P_{j-1} \\ R_{j-1} = s_{j-1}H_\rho(P_{j-1}) + c_{j-1}I & \\ c_j = H_s(m, L_{j-1}, R_{j-1}) & c_j = H_s(m, L_{j-1}) \end{array}$$

- Rationale for the calculation $c_j = H_s(m, L_{j-1}, R_{j-1})$
 - c_j 's should depend on I
 - Using something like $c_j = H_s(m, L_{j-1}, I)$ will not guarantee linkability

Multilayered LSAG Signatures

- Consider a transaction which unlocks funds in m one-time addresses
 - Each LSAG signature is of the form $\sigma = (l, c_0, s_0, s_1, \dots, s_{n-1})$ where n is the ring size
 - m LSAG signatures will take space $\mathcal{O}(m(n+2))$
- MLSAG signatures occupy space $\mathcal{O}(m(n+1))$
- MLSAG signatures are ring signatures over a set of n key-vectors
- Consider an $m \times n$ matrix of public keys

$$\begin{bmatrix} P_0^1 & P_1^1 & \dots & P_\pi^1 & \dots & P_{n-1}^1 \\ P_0^2 & P_1^2 & \dots & P_\pi^2 & \dots & P_{n-1}^2 \\ \vdots & \vdots & \dots & \vdots & \dots & \vdots \\ P_0^m & P_1^m & \dots & P_\pi^m & \dots & P_{n-1}^m \end{bmatrix}$$

where the signer knows x_π^j such that $P_\pi^j = x_\pi^j G$ for $j = 1, 2, \dots, m$

- An MLSAG signature scheme is linkable if usage of the same private key to create two signatures can be detected

MLSAG Signature Generation

- For a given message m , the signer generates the MLSAG signature as follows:

- Picks α_π^j and s_i^j randomly from \mathbb{Z}_L for $j = 1, \dots, m$ and $i = 1, \dots, n, i \neq \pi$
- Computes $L_\pi^j = \alpha_\pi^j G$, $R_\pi^j = \alpha_\pi^j H_p(P_\pi^j)$, $l_j = x_\pi^j H_p(P_\pi^j)$ and

$$c_{\pi+1} = H_s \left(m, L_\pi^1, R_\pi^1, \dots, L_\pi^m, R_\pi^m \right)$$

- Increasing π modulo n , computes

$$L_{\pi+1}^j = s_{\pi+1}^j G + c_{\pi+1} P_{\pi+1}^j$$

$$R_{\pi+1}^j = s_{\pi+1}^j H_p(P_{\pi+1}^j) + c_{\pi+1} l_j$$

$$c_{\pi+2} = H_s \left(m, L_{\pi+1}^1, R_{\pi+1}^1, \dots, L_{\pi+1}^m, R_{\pi+1}^m \right)$$

⋮

$$L_{\pi-1}^j = s_{\pi-1}^j G + c_{\pi-1} P_{\pi-1}^j$$

$$R_{\pi-1}^j = s_{\pi-1}^j H_p(P_{\pi-1}^j) + c_{\pi-1} l_j$$

$$c_\pi = H_s \left(m, L_{\pi-1}^1, R_{\pi-1}^1, \dots, L_{\pi-1}^m, R_{\pi-1}^m \right)$$

- Signer computes $s_\pi^j = \alpha_\pi^j - c_\pi x_\pi^j \bmod L$

- The ring signature is

$$\sigma = (l_1, \dots, l_m, c_0, s_0^1, \dots, s_0^m, s_1^1, \dots, s_1^m, s_{n-1}^1, \dots, s_{n-1}^m)$$

Deanononymization using Commitments

- Consider a confidential transaction which has two inputs and two outputs
- Suppose the sender uses a ring of size 5

$$\text{Public key matrix} = \begin{bmatrix} P_0^1 & P_1^1 & P_2^1 & P_3^1 & P_4^1 \\ P_0^2 & P_1^2 & P_2^2 & P_3^2 & P_4^2 \end{bmatrix}$$

and knows private keys for P_2^1, P_2^2

- Let input commitments be

$$\begin{bmatrix} (C_{in})_0^1 & (C_{in})_1^1 & (C_{in})_2^1 & (C_{in})_3^1 & (C_{in})_4^1 \\ (C_{in})_0^2 & (C_{in})_1^2 & (C_{in})_2^2 & (C_{in})_3^2 & (C_{in})_4^2 \end{bmatrix}$$

- Let output commitments be $(C_{out})^1, (C_{out})^2$ and fees be f
- Observer can identify the sender column by checking for each $k = 0, 1, 2, 3, 4$ if

$$(C_{in})_k^1 + (C_{in})_k^2 = (C_{out})^1 + (C_{out})^2 + fH$$

- We need to prove that the commitments in a column add up without revealing the column

Monero RingCT

- Previously, to ensure $(C_{in})_{\pi}^1 + (C_{in})_{\pi}^2 = (C_{out})^1 + (C_{out})^2 + fH$, blinding factors need to be balanced

$$(x_{in})_{\pi}^1 + (x_{in})_{\pi}^2 = (x_{out})^1 + (x_{out})^2$$

- Balancing needed only for third party verification of transactions
- For anonymization, we can set $(x_{in})_{\pi}^1 + (x_{in})_{\pi}^2 = (x_{out})^1 + (x_{out})^2 + z$ and communicate z to receiver using the shared secret
- How to enable third party verification?
- Solution:** MLSAG using following public key matrix

$$\begin{bmatrix} P_0^1 & P_1^1 & P_2^1 & P_3^1 & P_4^1 \\ P_0^2 & P_1^2 & P_2^2 & P_3^2 & P_4^2 \\ \sum_{j=1}^2 (C_{in})_0^j - \sum_{j=1}^2 (C_{out})^j - fH & \dots & \dots & \dots & \sum_{j=1}^2 (C_{in})_4^j - \sum_{j=1}^2 (C_{out})^j - fH \end{bmatrix}$$

- A signature verifiable using a public key in the last row implies knowledge of corresponding z

References

- **Ring Confidential Transactions** <http://www.ledgerjournal.org/ojs/index.php/ledger/article/view/34>
- **LSAG, Part 6 of Monero's Building Blocks Articles** https://delfr.com/wp-content/uploads/2018/04/Monero_Building_Blocks_Part6.pdf
- **MLSAG, Part 7 of Monero's Building Blocks Articles** https://delfr.com/wp-content/uploads/2018/05/Monero_Building_Blocks_Part7.pdf
- **RingCT, Part 9 of Monero's Building Blocks Articles** https://delfr.com/wp-content/uploads/2018/04/Monero_Building_Blocks_Part9.pdf