

SEMICONDUCTOR DEVICES

Introduction to Semiconductors



M. B. Patil

mbpatil@ee.iitb.ac.in

www.ee.iitb.ac.in/~sequel

Department of Electrical Engineering
Indian Institute of Technology Bombay

- * highly specialised and sophisticated

- * highly specialised and sophisticated
- * involves many branches of science and engineering

- * highly specialised and sophisticated
- * involves many branches of science and engineering
- * Silicon is the most commonly used semiconductor for fabrication of devices and ICs

- * highly specialised and sophisticated
- * involves many branches of science and engineering
- * Silicon is the most commonly used semiconductor for fabrication of devices and ICs
 - abundance in nature

- * highly specialised and sophisticated
- * involves many branches of science and engineering
- * Silicon is the most commonly used semiconductor for fabrication of devices and ICs
 - abundance in nature
 - fairly good material properties

- * highly specialised and sophisticated
- * involves many branches of science and engineering
- * Silicon is the most commonly used semiconductor for fabrication of devices and ICs
 - abundance in nature
 - fairly good material properties
 - can be easily doped (made p - or n -type)

- * highly specialised and sophisticated
- * involves many branches of science and engineering
- * Silicon is the most commonly used semiconductor for fabrication of devices and ICs
 - abundance in nature
 - fairly good material properties
 - can be easily doped (made p - or n -type)
 - SiO_2 is easy to deposit or grow on silicon, and it is used

- * highly specialised and sophisticated
- * involves many branches of science and engineering
- * Silicon is the most commonly used semiconductor for fabrication of devices and ICs
 - abundance in nature
 - fairly good material properties
 - can be easily doped (made p - or n -type)
 - SiO_2 is easy to deposit or grow on silicon, and it is used
 - ◇ for photolithography (making patterns)

- * highly specialised and sophisticated
- * involves many branches of science and engineering
- * Silicon is the most commonly used semiconductor for fabrication of devices and ICs
 - abundance in nature
 - fairly good material properties
 - can be easily doped (made p - or n -type)
 - SiO_2 is easy to deposit or grow on silicon, and it is used
 - ◇ for photolithography (making patterns)
 - ◇ as part of the MOS devices

- * highly specialised and sophisticated
- * involves many branches of science and engineering
- * Silicon is the most commonly used semiconductor for fabrication of devices and ICs
 - abundance in nature
 - fairly good material properties
 - can be easily doped (made p - or n -type)
 - SiO_2 is easy to deposit or grow on silicon, and it is used
 - ◇ for photolithography (making patterns)
 - ◇ as part of the MOS devices
 - ◇ to provide isolation between devices in an IC

- * highly specialised and sophisticated
- * involves many branches of science and engineering
- * Silicon is the most commonly used semiconductor for fabrication of devices and ICs
 - abundance in nature
 - fairly good material properties
 - can be easily doped (made p - or n -type)
 - SiO_2 is easy to deposit or grow on silicon, and it is used
 - ◇ for photolithography (making patterns)
 - ◇ as part of the MOS devices
 - ◇ to provide isolation between devices in an IC
- * Other semiconductors (e.g., GaAs, InP, GaN, SiC) are used when silicon is not suitable. Examples include

- * highly specialised and sophisticated
- * involves many branches of science and engineering
- * Silicon is the most commonly used semiconductor for fabrication of devices and ICs
 - abundance in nature
 - fairly good material properties
 - can be easily doped (made p - or n -type)
 - SiO_2 is easy to deposit or grow on silicon, and it is used
 - ◇ for photolithography (making patterns)
 - ◇ as part of the MOS devices
 - ◇ to provide isolation between devices in an IC
- * Other semiconductors (e.g., GaAs, InP, GaN, SiC) are used when silicon is not suitable. Examples include
 - optoelectronic devices (LEDs, lasers, optical modulators, etc.)

- * highly specialised and sophisticated
- * involves many branches of science and engineering
- * Silicon is the most commonly used semiconductor for fabrication of devices and ICs
 - abundance in nature
 - fairly good material properties
 - can be easily doped (made p - or n -type)
 - SiO_2 is easy to deposit or grow on silicon, and it is used
 - ◇ for photolithography (making patterns)
 - ◇ as part of the MOS devices
 - ◇ to provide isolation between devices in an IC
- * Other semiconductors (e.g., GaAs, InP, GaN, SiC) are used when silicon is not suitable. Examples include
 - optoelectronic devices (LEDs, lasers, optical modulators, etc.)
 - high-voltage power devices

- * highly specialised and sophisticated
- * involves many branches of science and engineering
- * Silicon is the most commonly used semiconductor for fabrication of devices and ICs
 - abundance in nature
 - fairly good material properties
 - can be easily doped (made p - or n -type)
 - SiO_2 is easy to deposit or grow on silicon, and it is used
 - ◇ for photolithography (making patterns)
 - ◇ as part of the MOS devices
 - ◇ to provide isolation between devices in an IC
- * Other semiconductors (e.g., GaAs, InP, GaN, SiC) are used when silicon is not suitable. Examples include
 - optoelectronic devices (LEDs, lasers, optical modulators, etc.)
 - high-voltage power devices
 - high-frequency devices such as heterojunction bipolar transistors and high electron mobility transistors

- * highly specialised and sophisticated
- * involves many branches of science and engineering
- * Silicon is the most commonly used semiconductor for fabrication of devices and ICs
 - abundance in nature
 - fairly good material properties
 - can be easily doped (made p - or n -type)
 - SiO_2 is easy to deposit or grow on silicon, and it is used
 - ◇ for photolithography (making patterns)
 - ◇ as part of the MOS devices
 - ◇ to provide isolation between devices in an IC
- * Other semiconductors (e.g., GaAs, InP, GaN, SiC) are used when silicon is not suitable. Examples include
 - optoelectronic devices (LEDs, lasers, optical modulators, etc.)
 - high-voltage power devices
 - high-frequency devices such as heterojunction bipolar transistors and high electron mobility transistors
 - high-efficiency solar cells

- * Dimensions

- * Dimensions

- $50\text{ }\mu\text{m}$ to $100\text{ }\mu\text{m}$ (0.05 mm to 0.1 mm): diameter of human hair

- * Dimensions

- 50 μm to 100 μm (0.05 mm to 0.1 mm): diameter of human hair
- 6 μm to 8 μm : size of a red blood cell

* Dimensions

- 50 μm to 100 μm (0.05 mm to 0.1 mm): diameter of human hair
- 6 μm to 8 μm : size of a red blood cell
- 0.2 μm to 2 μm : size of a bacterium

* Dimensions

- 50 μm to 100 μm (0.05 mm to 0.1 mm): diameter of human hair
- 6 μm to 8 μm : size of a red blood cell
- 0.2 μm to 2 μm : size of a bacterium
- 0.02 μm to 0.4 μm : size of a virus

* Dimensions

- 50 μm to 100 μm (0.05 mm to 0.1 mm): diameter of human hair
- 6 μm to 8 μm : size of a red blood cell
- 0.2 μm to 2 μm : size of a bacterium
- 0.02 μm to 0.4 μm : size of a virus
- 10 μm : minimum feature size in an IC in 1970

* Dimensions

- 50 μm to 100 μm (0.05 mm to 0.1 mm): diameter of human hair
- 6 μm to 8 μm : size of a red blood cell
- 0.2 μm to 2 μm : size of a bacterium
- 0.02 μm to 0.4 μm : size of a virus
- 10 μm : minimum feature size in an IC in 1970
- 32 nm (0.032 μm): minimum feature size in an IC in 2010

* Dimensions

- 50 μm to 100 μm (0.05 mm to 0.1 mm): diameter of human hair
- 6 μm to 8 μm : size of a red blood cell
- 0.2 μm to 2 μm : size of a bacterium
- 0.02 μm to 0.4 μm : size of a virus
- 10 μm : minimum feature size in an IC in 1970
- 32 nm (0.032 μm): minimum feature size in an IC in 2010
- $\sim 5 \text{ \AA}$ (0.5 nm): interatomic distance in a silicon crystal

* Dimensions

- 50 μm to 100 μm (0.05 mm to 0.1 mm): diameter of human hair
- 6 μm to 8 μm : size of a red blood cell
- 0.2 μm to 2 μm : size of a bacterium
- 0.02 μm to 0.4 μm : size of a virus
- 10 μm : minimum feature size in an IC in 1970
- 32 nm (0.032 μm): minimum feature size in an IC in 2010
- $\sim 5 \text{ \AA}$ (0.5 nm): interatomic distance in a silicon crystal

* Densities (Area)

* Dimensions

- $50\text{ }\mu\text{m}$ to $100\text{ }\mu\text{m}$ (0.05 mm to 0.1 mm): diameter of human hair
- $6\text{ }\mu\text{m}$ to $8\text{ }\mu\text{m}$: size of a red blood cell
- $0.2\text{ }\mu\text{m}$ to $2\text{ }\mu\text{m}$: size of a bacterium
- $0.02\text{ }\mu\text{m}$ to $0.4\text{ }\mu\text{m}$: size of a virus
- $10\text{ }\mu\text{m}$: minimum feature size in an IC in 1970
- 32 nm ($0.032\text{ }\mu\text{m}$): minimum feature size in an IC in 2010
- $\sim 5\text{ \AA}$ (0.5 nm): interatomic distance in a silicon crystal

* Densities (Area)

- $350/\text{cm}^2$: hair density for a youngster

* Dimensions

- $50\text{ }\mu\text{m}$ to $100\text{ }\mu\text{m}$ (0.05 mm to 0.1 mm): diameter of human hair
- $6\text{ }\mu\text{m}$ to $8\text{ }\mu\text{m}$: size of a red blood cell
- $0.2\text{ }\mu\text{m}$ to $2\text{ }\mu\text{m}$: size of a bacterium
- $0.02\text{ }\mu\text{m}$ to $0.4\text{ }\mu\text{m}$: size of a virus
- $10\text{ }\mu\text{m}$: minimum feature size in an IC in 1970
- 32 nm ($0.032\text{ }\mu\text{m}$): minimum feature size in an IC in 2010
- $\sim 5\text{ \AA}$ (0.5 nm): interatomic distance in a silicon crystal

* Densities (Area)

- $350/\text{cm}^2$: hair density for a youngster
- $1500/\text{cm}^2$: number of pixels in an LCD monitor

* Dimensions

- $50\text{ }\mu\text{m}$ to $100\text{ }\mu\text{m}$ (0.05 mm to 0.1 mm): diameter of human hair
- $6\text{ }\mu\text{m}$ to $8\text{ }\mu\text{m}$: size of a red blood cell
- $0.2\text{ }\mu\text{m}$ to $2\text{ }\mu\text{m}$: size of a bacterium
- $0.02\text{ }\mu\text{m}$ to $0.4\text{ }\mu\text{m}$: size of a virus
- $10\text{ }\mu\text{m}$: minimum feature size in an IC in 1970
- 32 nm ($0.032\text{ }\mu\text{m}$): minimum feature size in an IC in 2010
- $\sim 5\text{ \AA}$ (0.5 nm): interatomic distance in a silicon crystal

* Densities (Area)

- $350/\text{cm}^2$: hair density for a youngster
- $1500/\text{cm}^2$: number of pixels in an LCD monitor
- $10^7/\text{cm}^2$: number of MOS transistors in a modern processor chip

- * Electrical power

- * Electrical power

- $\sim 300 \times 10^9$ W (300 GW): total installed electricity generation capacity in India as on May 2017

- * Electrical power

- $\sim 300 \times 10^9 \text{ W}$ (300 GW): total installed electricity generation capacity in India as on May 2017
- $\sim 3.3 \times 10^9 \text{ W}$ (3.3 GW or 3,300 MW): average electricity consumption of Mumbai as on May 2017

* Electrical power

- $\sim 300 \times 10^9 \text{ W}$ (300 GW): total installed electricity generation capacity in India as on May 2017
- $\sim 3.3 \times 10^9 \text{ W}$ (3.3 GW or 3,300 MW): average electricity consumption of Mumbai as on May 2017
- $\sim 2 \times 10^3 \text{ W}$ (2 kW): power consumption of a 1.5 tonne air conditioner

* Electrical power

- $\sim 300 \times 10^9 \text{ W}$ (300 GW): total installed electricity generation capacity in India as on May 2017
- $\sim 3.3 \times 10^9 \text{ W}$ (3.3 GW or 3,300 MW): average electricity consumption of Mumbai as on May 2017
- $\sim 2 \times 10^3 \text{ W}$ (2 kW): power consumption of a 1.5 tonne air conditioner
- 100 W: consumption of an incandescent bulb giving 1,600 lumens

* Electrical power

- $\sim 300 \times 10^9 \text{ W}$ (300 GW): total installed electricity generation capacity in India as on May 2017
- $\sim 3.3 \times 10^9 \text{ W}$ (3.3 GW or 3,300 MW): average electricity consumption of Mumbai as on May 2017
- $\sim 2 \times 10^3 \text{ W}$ (2 kW): power consumption of a 1.5 tonne air conditioner
- 100 W: consumption of an incandescent bulb giving 1,600 lumens
- 23 to 27 W: consumption of a compact fluorescent lamp (CFL) giving 1,600 lumens

* Electrical power

- $\sim 300 \times 10^9 \text{ W}$ (300 GW): total installed electricity generation capacity in India as on May 2017
- $\sim 3.3 \times 10^9 \text{ W}$ (3.3 GW or 3,300 MW): average electricity consumption of Mumbai as on May 2017
- $\sim 2 \times 10^3 \text{ W}$ (2 kW): power consumption of a 1.5 tonne air conditioner
- 100 W: consumption of an incandescent bulb giving 1,600 lumens
- 23 to 27 W: consumption of a compact fluorescent lamp (CFL) giving 1,600 lumens
- 15 to 22 W: consumption of LED lamp giving 1,600 lumens

* Electrical power

- $\sim 300 \times 10^9$ W (300 GW): total installed electricity generation capacity in India as on May 2017
- $\sim 3.3 \times 10^9$ W (3.3 GW or 3,300 MW): average electricity consumption of Mumbai as on May 2017
- $\sim 2 \times 10^3$ W (2 kW): power consumption of a 1.5 tonne air conditioner
- 100 W: consumption of an incandescent bulb giving 1,600 lumens
- 23 to 27 W: consumption of a compact fluorescent lamp (CFL) giving 1,600 lumens
- 15 to 22 W: consumption of LED lamp giving 1,600 lumens
- ~ 1 W: power consumption of a low-power triode

* Electrical power

- $\sim 300 \times 10^9$ W (300 GW): total installed electricity generation capacity in India as on May 2017
- $\sim 3.3 \times 10^9$ W (3.3 GW or 3,300 MW): average electricity consumption of Mumbai as on May 2017
- $\sim 2 \times 10^3$ W (2 kW): power consumption of a 1.5 tonne air conditioner
- 100 W: consumption of an incandescent bulb giving 1,600 lumens
- 23 to 27 W: consumption of a compact fluorescent lamp (CFL) giving 1,600 lumens
- 15 to 22 W: consumption of LED lamp giving 1,600 lumens
- ~ 1 W: power consumption of a low-power triode
- 100 μ W: average power consumption per transistor in a MOS microprocessor IC in 1970

* Electrical power

- $\sim 300 \times 10^9$ W (300 GW): total installed electricity generation capacity in India as on May 2017
- $\sim 3.3 \times 10^9$ W (3.3 GW or 3,300 MW): average electricity consumption of Mumbai as on May 2017
- $\sim 2 \times 10^3$ W (2 kW): power consumption of a 1.5 tonne air conditioner
- 100 W: consumption of an incandescent bulb giving 1,600 lumens
- 23 to 27 W: consumption of a compact fluorescent lamp (CFL) giving 1,600 lumens
- 15 to 22 W: consumption of LED lamp giving 1,600 lumens
- ~ 1 W: power consumption of a low-power triode
- 100 μ W: average power consumption per transistor in a MOS microprocessor IC in 1970
- 20 nW: average power consumption per transistor in a MOS microprocessor IC in 2010

- * Voltage

- * Voltage
 - ~ 100 kV: voltage used in long-distance transmission

- * Voltage

- ~ 100 kV: voltage used in long-distance transmission
- 25 kV (AC): voltage used for electric traction in India (long-distance trains)

- * Voltage

- ~ 100 kV: voltage used in long-distance transmission
- 25 kV (AC): voltage used for electric traction in India (long-distance trains)
- 230 V (AC): domestic supply voltage in India

* Voltage

- ~ 100 kV: voltage used in long-distance transmission
- 25 kV (AC): voltage used for electric traction in India (long-distance trains)
- 230 V (AC): domestic supply voltage in India
- ~ 100 V: vacuum tube operating voltage for audio applications

* Voltage

- ~ 100 kV: voltage used in long-distance transmission
- 25 kV (AC): voltage used for electric traction in India (long-distance trains)
- 230 V (AC): domestic supply voltage in India
- ~ 100 V: vacuum tube operating voltage for audio applications
- 5 V to 15 V: operating voltage for modern electronics using semiconductor devices and ICs

* Voltage

- ~ 100 kV: voltage used in long-distance transmission
- 25 kV (AC): voltage used for electric traction in India (long-distance trains)
- 230 V (AC): domestic supply voltage in India
- ~ 100 V: vacuum tube operating voltage for audio applications
- 5 V to 15 V: operating voltage for modern electronics using semiconductor devices and ICs
- 1.1 V: supply voltage in low-power CMOS ICs in 2010

* Voltage

- ~ 100 kV: voltage used in long-distance transmission
- 25 kV (AC): voltage used for electric traction in India (long-distance trains)
- 230 V (AC): domestic supply voltage in India
- ~ 100 V: vacuum tube operating voltage for audio applications
- 5 V to 15 V: operating voltage for modern electronics using semiconductor devices and ICs
- 1.1 V: supply voltage in low-power CMOS ICs in 2010
- ~ 100 mV: action potential (nerve impulse) in neurons which is responsible for cell-to-cell communication

* Voltage

- ~ 100 kV: voltage used in long-distance transmission
- 25 kV (AC): voltage used for electric traction in India (long-distance trains)
- 230 V (AC): domestic supply voltage in India
- ~ 100 V: vacuum tube operating voltage for audio applications
- 5 V to 15 V: operating voltage for modern electronics using semiconductor devices and ICs
- 1.1 V: supply voltage in low-power CMOS ICs in 2010
- ~ 100 mV: action potential (nerve impulse) in neurons which is responsible for cell-to-cell communication
- ~ 1 μ V: signal received by a mobile phone

- * Current

- * Current
 - 30 kA to 300 kA: current carried by a bolt of lightning

- * Current

- 30 kA to 300 kA: current carried by a bolt of lightning
- 500 A to 1500 A: current carrying capacity of transmission lines

* Current

- 30 kA to 300 kA: current carried by a bolt of lightning
- 500 A to 1500 A: current carrying capacity of transmission lines
- ~ 2000 A: maximum current that can be carried by a power semiconductor device

* Current

- 30 kA to 300 kA: current carried by a bolt of lightning
- 500 A to 1500 A: current carrying capacity of transmission lines
- ~ 2000 A: maximum current that can be carried by a power semiconductor device
- ~ 50 mA: fatal current for the human body

* Current

- 30 kA to 300 kA: current carried by a bolt of lightning
- 500 A to 1500 A: current carrying capacity of transmission lines
- ~ 2000 A: maximum current that can be carried by a power semiconductor device
- ~ 50 mA: fatal current for the human body
- ~ 20 mA: current required for an LED to glow brightly

* Current

- 30 kA to 300 kA: current carried by a bolt of lightning
- 500 A to 1500 A: current carrying capacity of transmission lines
- ~ 2000 A: maximum current that can be carried by a power semiconductor device
- ~ 50 mA: fatal current for the human body
- ~ 20 mA: current required for an LED to glow brightly
- ~ 1 μ A: average transistor current in a modern processor IC

* Current

- 30 kA to 300 kA: current carried by a bolt of lightning
- 500 A to 1500 A: current carrying capacity of transmission lines
- ~ 2000 A: maximum current that can be carried by a power semiconductor device
- ~ 50 mA: fatal current for the human body
- ~ 20 mA: current required for an LED to glow brightly
- ~ 1 μ A: average transistor current in a modern processor IC

* Energy

* Current

- 30 kA to 300 kA: current carried by a bolt of lightning
- 500 A to 1500 A: current carrying capacity of transmission lines
- ~ 2000 A: maximum current that can be carried by a power semiconductor device
- ~ 50 mA: fatal current for the human body
- ~ 20 mA: current required for an LED to glow brightly
- ~ 1 μ A: average transistor current in a modern processor IC

* Energy

- 1.1 eV: band gap of silicon ($1 \text{ eV} = 1.6 \times 10^{-19} \text{ J}$)

* Current

- 30 kA to 300 kA: current carried by a bolt of lightning
- 500 A to 1500 A: current carrying capacity of transmission lines
- ~ 2000 A: maximum current that can be carried by a power semiconductor device
- ~ 50 mA: fatal current for the human body
- ~ 20 mA: current required for an LED to glow brightly
- ~ 1 μ A: average transistor current in a modern processor IC

* Energy

- 1.1 eV: band gap of silicon ($1 \text{ eV} = 1.6 \times 10^{-19} \text{ J}$)
- 1.65 eV to 3.27 eV: photon energy in the visible range

* Current

- 30 kA to 300 kA: current carried by a bolt of lightning
- 500 A to 1500 A: current carrying capacity of transmission lines
- ~ 2000 A: maximum current that can be carried by a power semiconductor device
- ~ 50 mA: fatal current for the human body
- ~ 20 mA: current required for an LED to glow brightly
- ~ 1 μ A: average transistor current in a modern processor IC

* Energy

- 1.1 eV: band gap of silicon ($1 \text{ eV} = 1.6 \times 10^{-19} \text{ J}$)
- 1.65 eV to 3.27 eV: photon energy in the visible range
- 13.6 eV: binding energy of an electron in the ground state of the hydrogen atom, i.e., energy required to set the electron free of the influence of the nucleus

* Current

- 30 kA to 300 kA: current carried by a bolt of lightning
- 500 A to 1500 A: current carrying capacity of transmission lines
- ~ 2000 A: maximum current that can be carried by a power semiconductor device
- ~ 50 mA: fatal current for the human body
- ~ 20 mA: current required for an LED to glow brightly
- ~ 1 μ A: average transistor current in a modern processor IC

* Energy

- 1.1 eV: band gap of silicon ($1 \text{ eV} = 1.6 \times 10^{-19} \text{ J}$)
- 1.65 eV to 3.27 eV: photon energy in the visible range
- 13.6 eV: binding energy of an electron in the ground state of the hydrogen atom, i.e., energy required to set the electron free of the influence of the nucleus
- ~ 20 keV: energy of an electron striking the screen of a colour TV (CRT type)

* Current

- 30 kA to 300 kA: current carried by a bolt of lightning
- 500 A to 1500 A: current carrying capacity of transmission lines
- ~ 2000 A: maximum current that can be carried by a power semiconductor device
- ~ 50 mA: fatal current for the human body
- ~ 20 mA: current required for an LED to glow brightly
- ~ 1 μ A: average transistor current in a modern processor IC

* Energy

- 1.1 eV: band gap of silicon ($1 \text{ eV} = 1.6 \times 10^{-19} \text{ J}$)
- 1.65 eV to 3.27 eV: photon energy in the visible range
- 13.6 eV: binding energy of an electron in the ground state of the hydrogen atom, i.e., energy required to set the electron free of the influence of the nucleus
- ~ 20 keV: energy of an electron striking the screen of a colour TV (CRT type)
- ~ 200 keV: photon energy for X-rays used in medical diagnosis

- * Temperature

- * Temperature

- 0 °C to 70 °C: operating temperature range for a commercial-grade semiconductor device

- * Temperature

- 0 °C to 70 °C: operating temperature range for a commercial-grade semiconductor device
- –55 °C to 125 °C: operating temperature range for a military-grade semiconductor device

- * Temperature

- 0 °C to 70 °C: operating temperature range for a commercial-grade semiconductor device
- –55 °C to 125 °C: operating temperature range for a military-grade semiconductor device
- 800 °C to 1000 °C: typical furnace temperatures used in IC technology

* Temperature

- 0°C to 70°C : operating temperature range for a commercial-grade semiconductor device
- -55°C to 125°C : operating temperature range for a military-grade semiconductor device
- 800°C to 1000°C : typical furnace temperatures used in IC technology
- $\sim 1400^{\circ}\text{C}$: melting point of silicon

- * Temperature

- 0 °C to 70 °C: operating temperature range for a commercial-grade semiconductor device
- –55 °C to 125 °C: operating temperature range for a military-grade semiconductor device
- 800 °C to 1000 °C: typical furnace temperatures used in IC technology
- ~ 1400 °C: melting point of silicon

- * Frequency

- * Temperature

- 0°C to 70°C : operating temperature range for a commercial-grade semiconductor device
- -55°C to 125°C : operating temperature range for a military-grade semiconductor device
- 800°C to 1000°C : typical furnace temperatures used in IC technology
- $\sim 1400^{\circ}\text{C}$: melting point of silicon

- * Frequency

- $4 \times 10^{14} \text{ Hz}$ to $8 \times 10^{14} \text{ Hz}$: frequency of visible light

* Temperature

- 0°C to 70°C : operating temperature range for a commercial-grade semiconductor device
- -55°C to 125°C : operating temperature range for a military-grade semiconductor device
- 800°C to 1000°C : typical furnace temperatures used in IC technology
- $\sim 1400^{\circ}\text{C}$: melting point of silicon

* Frequency

- 4×10^{14} Hz to 8×10^{14} Hz: frequency of visible light
- 20 Hz to 20 kHz: frequency range of hearing for humans

* Temperature

- 0°C to 70°C : operating temperature range for a commercial-grade semiconductor device
- -55°C to 125°C : operating temperature range for a military-grade semiconductor device
- 800°C to 1000°C : typical furnace temperatures used in IC technology
- $\sim 1400^{\circ}\text{C}$: melting point of silicon

* Frequency

- 4×10^{14} Hz to 8×10^{14} Hz: frequency of visible light
- 20 Hz to 20 kHz: frequency range of hearing for humans
- 70 Hz to 150 kHz: frequency range of hearing for whales and dolphins

* Temperature

- 0°C to 70°C : operating temperature range for a commercial-grade semiconductor device
- -55°C to 125°C : operating temperature range for a military-grade semiconductor device
- 800°C to 1000°C : typical furnace temperatures used in IC technology
- $\sim 1400^{\circ}\text{C}$: melting point of silicon

* Frequency

- 4×10^{14} Hz to 8×10^{14} Hz: frequency of visible light
- 20 Hz to 20 kHz: frequency range of hearing for humans
- 70 Hz to 150 kHz: frequency range of hearing for whales and dolphins
- 535 kHz to 1605 kHz: AM radio frequency range (Medium Wave)

* Temperature

- 0 °C to 70 °C: operating temperature range for a commercial-grade semiconductor device
- –55 °C to 125 °C: operating temperature range for a military-grade semiconductor device
- 800 °C to 1000 °C: typical furnace temperatures used in IC technology
- ~ 1400 °C: melting point of silicon

* Frequency


- 4×10^{14} Hz to 8×10^{14} Hz: frequency of visible light
- 20 Hz to 20 kHz: frequency range of hearing for humans
- 70 Hz to 150 kHz: frequency range of hearing for whales and dolphins
- 535 kHz to 1605 kHz: AM radio frequency range (Medium Wave)
- 88 MHz to 108 MHz: FM radio frequency range


* Temperature

- 0°C to 70°C : operating temperature range for a commercial-grade semiconductor device
- -55°C to 125°C : operating temperature range for a military-grade semiconductor device
- 800°C to 1000°C : typical furnace temperatures used in IC technology
- $\sim 1400^{\circ}\text{C}$: melting point of silicon


* Frequency

- 4×10^{14} Hz to 8×10^{14} Hz: frequency of visible light
- 20 Hz to 20 kHz: frequency range of hearing for humans
- 70 Hz to 150 kHz: frequency range of hearing for whales and dolphins
- 535 kHz to 1605 kHz: AM radio frequency range (Medium Wave)
- 88 MHz to 108 MHz: FM radio frequency range
- ~ 900 MHz: frequency for mobile communication (GSM standard)






Electric field $\mathcal{E} = \frac{V}{L}$ (assuming uniform current flow).



Electric field $\mathcal{E} = \frac{V}{L}$ (assuming uniform current flow).

$I = A \sigma \mathcal{E}$, where σ is the conductivity in $(\Omega\text{-cm})^{-1}$.



Electric field $\mathcal{E} = \frac{V}{L}$ (assuming uniform current flow).


$I = A \sigma \mathcal{E}$, where σ is the conductivity in $(\Omega\text{-cm})^{-1}$.

Material	Type	$\sigma (\Omega\text{-cm})^{-1}$
Copper	conductor	$\sim 6 \times 10^5$
Glass	insulator	10^{-17} to 10^{-13}
Silicon	semiconductor	$\sim 10^{-5}$


Solids may be classified as

- * Crystalline: Atoms are arranged in a periodic manner.


Crystalline



Polycrystalline



Amorphous




(Ref.: wikipedia)


Solids may be classified as

- * Crystalline: Atoms are arranged in a periodic manner.
- * Polycrystalline: The solid contains many crystallites which vary in size and orientation.


Crystalline



Polycrystalline



Amorphous




(Ref.: wikipedia)


Solids may be classified as

- * Crystalline: Atoms are arranged in a periodic manner.
- * Polycrystalline: The solid contains many crystallites which vary in size and orientation.
- * Amorphous: There is no long-range order.


Crystalline



Polycrystalline



Amorphous




(Ref.: wikipedia)

Solids may be classified as

- * Crystalline: Atoms are arranged in a periodic manner.
- * Polycrystalline: The solid contains many crystallites which vary in size and orientation.
- * Amorphous: There is no long-range order.

Crystalline semiconductors have superior material properties, leading to higher device performance.




(Ref.: wikipedia)

Solids may be classified as

- * Crystalline: Atoms are arranged in a periodic manner.
- * Polycrystalline: The solid contains many crystallites which vary in size and orientation.
- * Amorphous: There is no long-range order.



Crystalline semiconductors have superior material properties, leading to higher device performance.

Polycrystalline and amorphous semiconductors have relatively poor properties, but the ease of manufacturing and low cost makes them attractive for certain applications. e.g., as solar cells, thin-film transistors for display devices.




(Ref.: wikipedia)

Crystal structure of Si and GaAs




* Si and GaAs have the diamond structure.

Crystal structure of Si and GaAs




FCC lattice




Diamond structure

- * Si and GaAs have the diamond structure.
- * There are two identical FCC lattices, with lattice 2 displaced with respect to lattice 1 by one-fourth of the body diagonal.

Crystal structure of Si and GaAs




FCC lattice




Diamond structure

- * Si and GaAs have the diamond structure.
- * There are two identical FCC lattices, with lattice 2 displaced with respect to lattice 1 by one-fourth of the body diagonal.
- * Each silicon atom has four nearest neighbours, and it is bonded to the neighbours by strong covalent bonds.

Crystal structure of Si and GaAs




FCC lattice




Diamond structure


- * Si and GaAs have the diamond structure.
- * There are two identical FCC lattices, with lattice 2 displaced with respect to lattice 1 by one-fourth of the body diagonal.
- * Each silicon atom has four nearest neighbours, and it is bonded to the neighbours by strong covalent bonds.
- * The structure of GaAs is similar. Each Ga atom has four As neighbours, and *vice versa*.




FCC lattice



Diamond structure




FCC lattice




Diamond structure

* In silicon, the distance between neighbouring atoms is $\sqrt{3}a/4$, with $a = 5.43 \text{ \AA}$.




FCC lattice



Diamond structure


- * In silicon, the distance between neighbouring atoms is $\sqrt{3}a/4$, with $a = 5.43 \text{ \AA}$.
- * There are 5×10^{22} atoms per cm^3 .

Electrons and holes: the bond picture



2-D representation of silicon lattice


Electrons and holes: the bond picture



2-D representation of silicon lattice

- * Each silicon atom has a “core” part (nucleus + core electrons), and four “valence” electrons.


Electrons and holes: the bond picture



2-D representation of silicon lattice

- * Each silicon atom has a “core” part (nucleus + core electrons), and four “valence” electrons.
- * Core electrons are tightly bound to the nucleus and do not participate in conduction.


Electrons and holes: the bond picture



2-D representation of silicon lattice

- * Each silicon atom has a “core” part (nucleus + core electrons), and four “valence” electrons.
- * Core electrons are tightly bound to the nucleus and do not participate in conduction.
- * Valence electrons, which are in the outermost orbit, are available for bonding with other atoms.


Electrons and holes: the bond picture




2-D representation of silicon lattice

- * Each silicon atom has a “core” part (nucleus + core electrons), and four “valence” electrons.
- * Core electrons are tightly bound to the nucleus and do not participate in conduction.
- * Valence electrons, which are in the outermost orbit, are available for bonding with other atoms.
- * At 0 K, all valence electrons are held by the covalent bonds, no electrons are available for conduction, and the material behaves like an insulator.

Electrons and holes: the bond picture




Electrons and holes: the bond picture




- * A small fraction of the valence electrons (about 10^{10} cm^{-3} or one per 5×10^{12} atoms at 300 K) have enough energy to break free from the bonds.

Electrons and holes: the bond picture




- * A small fraction of the valence electrons (about 10^{10} cm^{-3} or one per 5×10^{12} atoms at 300 K) have enough energy to break free from the bonds.
- * When a valence electron breaks free, it leaves behind a vacancy or a “hole.”

Electrons and holes: the bond picture




- * A small fraction of the valence electrons (about 10^{10} cm^{-3} or one per 5×10^{12} atoms at 300 K) have enough energy to break free from the bonds.
- * When a valence electron breaks free, it leaves behind a vacancy or a “hole.”
- * These free electrons and holes are available for conduction.

Electrons and holes: the bond picture



Suppose one of the silicon atoms is replaced with a group V atom (e.g., P or As).


Electrons and holes: the bond picture



Suppose one of the silicon atoms is replaced with a group V atom (e.g., P or As).

- * The group V “impurity” atom has five valence electrons.


Electrons and holes: the bond picture



Suppose one of the silicon atoms is replaced with a group V atom (e.g., P or As).

- * The group V “impurity” atom has five valence electrons.
- * Four of these are shared with the neighbouring silicon atoms.


Electrons and holes: the bond picture



Suppose one of the silicon atoms is replaced with a group V atom (e.g., P or As).

- * The group V “impurity” atom has five valence electrons.
- * Four of these are shared with the neighbouring silicon atoms.
- * The fifth electron is relatively loosely bound to the impurity atom, and at room temperature, it can become free of the influence of the impurity atom.


Electrons and holes: the bond picture



Suppose one of the silicon atoms is replaced with a group V atom (e.g., P or As).


- * The group V “impurity” atom has five valence electrons.
- * Four of these are shared with the neighbouring silicon atoms.
- * The fifth electron is relatively loosely bound to the impurity atom, and at room temperature, it can become free of the influence of the impurity atom.
- * We say that the group V atom has “donated” a free electron to the lattice which is available for conduction.

Electrons and holes: the bond picture



Suppose one of the silicon atoms is replaced with a group III atom (e.g., B).


Electrons and holes: the bond picture



Suppose one of the silicon atoms is replaced with a group III atom (e.g., B).

- * The group III “impurity” atom has three valence electrons.


Electrons and holes: the bond picture



Suppose one of the silicon atoms is replaced with a group III atom (e.g., B).

- * The group III “impurity” atom has three valence electrons.
- * These electrons are shared with the neighbouring silicon atoms.


Electrons and holes: the bond picture



Suppose one of the silicon atoms is replaced with a group III atom (e.g., B).

- * The group III “impurity” atom has three valence electrons.
- * These electrons are shared with the neighbouring silicon atoms.
- * One of the bonds remains unfulfilled, i.e., it has a vacancy (hole).


Electrons and holes: the bond picture



Suppose one of the silicon atoms is replaced with a group III atom (e.g., B).

- * The group III “impurity” atom has three valence electrons.
- * These electrons are shared with the neighbouring silicon atoms.
- * One of the bonds remains unfulfilled, i.e., it has a vacancy (hole).
- * At room temperature, an electron from a neighbouring bond can occupy this hole (vacancy), thus giving rise to conduction.

Electrons and holes: the bond picture



Suppose one of the silicon atoms is replaced with a group III atom (e.g., B).

- * The group III “impurity” atom has three valence electrons.
- * These electrons are shared with the neighbouring silicon atoms.
- * One of the bonds remains unfulfilled, i.e., it has a vacancy (hole).
- * At room temperature, an electron from a neighbouring bond can occupy this hole (vacancy), thus giving rise to conduction.
- * We say that the group III atom has “accepted” an electron from a Si-Si bond, which is equivalent to transferring the vacancy (hole) to that bond.

The bond picture of a semiconductor gives us some insight, but it leaves several questions unanswered.

The bond picture of a semiconductor gives us some insight, but it leaves several questions unanswered.

- * What makes a crystalline material a semiconductor (and not a metal or an insulator)?

The bond picture of a semiconductor gives us some insight, but it leaves several questions unanswered.

- * What makes a crystalline material a semiconductor (and not a metal or an insulator)?
- * How can we calculate the carrier (electron or hole) density?

The bond picture of a semiconductor gives us some insight, but it leaves several questions unanswered.

- * What makes a crystalline material a semiconductor (and not a metal or an insulator)?
- * How can we calculate the carrier (electron or hole) density?
- * How does the carrier density vary with temperature?


The bond picture of a semiconductor gives us some insight, but it leaves several questions unanswered.

- * What makes a crystalline material a semiconductor (and not a metal or an insulator)?
- * How can we calculate the carrier (electron or hole) density?
- * How does the carrier density vary with temperature?
- * How are the carriers distributed in energy?


The bond picture of a semiconductor gives us some insight, but it leaves several questions unanswered.

- * What makes a crystalline material a semiconductor (and not a metal or an insulator)?
- * How can we calculate the carrier (electron or hole) density?
- * How does the carrier density vary with temperature?
- * How are the carriers distributed in energy?
- * Can *any* group V atom serve as a donor in silicon?

Electrons and holes: the band picture




Electrons and holes: the band picture




- * For an isolated atom, the wave functions and energy levels for the electrons can be obtained from the Schrödinger equation.

Electrons and holes: the band picture




- * For an isolated atom, the wave functions and energy levels for the electrons can be obtained from the Schrödinger equation.
- * An electron can only occupy one of these wave functions ("orbit" or "state").

Electrons and holes: the band picture




- * For an isolated atom, the wave functions and energy levels for the electrons can be obtained from the Schrödinger equation.
- * An electron can only occupy one of these wave functions (“orbit” or “state”).
- * If two atoms are close to each other – such that their wave functions overlap – the Schrödinger equation must be solved for the combined system to obtain the new wave functions and energy levels.

Electrons and holes: the band picture




- * For an isolated atom, the wave functions and energy levels for the electrons can be obtained from the Schrödinger equation.
- * An electron can only occupy one of these wave functions (“orbit” or “state”).
- * If two atoms are close to each other – such that their wave functions overlap – the Schrödinger equation must be solved for the combined system to obtain the new wave functions and energy levels.
- * Each of the energy level splits into two levels (states).

Electrons and holes: the band picture




Electrons and holes: the band picture




- * In a crystal, the problem is much more complex since the wave functions of several atoms overlap.

Electrons and holes: the band picture




- * In a crystal, the problem is much more complex since the wave functions of several atoms overlap.
- * The original energy levels split into a large number of levels.

Electrons and holes: the band picture




- * In a crystal, the problem is much more complex since the wave functions of several atoms overlap.
- * The original energy levels split into a large number of levels.
- * The number of levels is so large that we can treat them as a *continuum* or “band” of levels (states).

Electrons and holes: the band picture




- * In a crystal, the problem is much more complex since the wave functions of several atoms overlap.
- * The original energy levels split into a large number of levels.
- * The number of levels is so large that we can treat them as a *continuum* or "band" of levels (states).
- * For semiconductors, the states get bunched such that, in a certain energy range, $E_v < E < E_c$, there are no states at all.


Electrons and holes: the band picture



Electrons and holes: the band picture




- * The bottom edge of the conduction band is denoted by E_c , and the top edge of the valence band by E_v .



- * The bottom edge of the conduction band is denoted by E_c , and the top edge of the valence band by E_v .
- * The difference $E_c - E_v$ is called the “energy gap” (E_g), and it plays a fundamental role in the electrical and optical properties of a semiconductor.


Electrons and holes: the band picture



Semiconductor	E_g (eV)
Ge	0.67
Si	1.1
GaAs	1.43
GaP	2.26
GaN	3.4

- * The bottom edge of the conduction band is denoted by E_c , and the top edge of the valence band by E_v .
- * The difference $E_c - E_v$ is called the “energy gap” (E_g), and it plays a fundamental role in the electrical and optical properties of a semiconductor.


Electrons and holes: the band picture



Filled and empty electron states at 0 K.

(Note: This is a schematic representation;
in reality, the density of states varies with E .)

Electrons and holes: the band picture




Filled and empty electron states at 0 K.

(Note: This is a schematic representation;
in reality, the density of states varies with E .)

- * At $T = 0$ K, the valence band is completely full of electrons, and the conduction band is completely empty.

Electrons and holes: the band picture




Filled and empty electron states at 0 K.

(Note: This is a schematic representation;
in reality, the density of states varies with E .)

- * At $T = 0$ K, the valence band is completely full of electrons, and the conduction band is completely empty.
- * There is no possibility of conduction.


Electrons and holes: the band picture



Filled and empty electron states at 300 K.

(Note: This is a schematic representation;
in reality, the density of states varies with E .)

Electrons and holes: the band picture




Filled and empty electron states at 300 K.

(Note: This is a schematic representation;
in reality, the density of states varies with E .)

- * As the lattice temperature is increased, the probability of occupation of conduction band states by electrons increases.

Electrons and holes: the band picture




Filled and empty electron states at 300 K.

(Note: This is a schematic representation;
in reality, the density of states varies with E .)

- * As the lattice temperature is increased, the probability of occupation of conduction band states by electrons increases.
- * In a pure or “intrinsic” semiconductor, the number of electrons in the conduction band must be equal to the number of vacancies (holes) in the valence band.

Electrons and holes: the band picture




Filled and empty electron states at 300 K.

(Note: This is a schematic representation;
in reality, the density of states varies with E .)

- * As the lattice temperature is increased, the probability of occupation of conduction band states by electrons increases.
- * In a pure or “intrinsic” semiconductor, the number of electrons in the conduction band must be equal to the number of vacancies (holes) in the valence band.
- * The density of electrons (or holes) in the above situation is denoted by n_i , the “intrinsic carrier concentration,” and it is about 10^{10} cm^{-3} for Si at $T = 300 \text{ K}$. (Note that it is much smaller than the density of silicon atoms in the crystal, i.e., $5 \times 10^{22} \text{ cm}^{-3}$).


Electrons and holes: the band picture



Filled and empty electron states at 300 K.

(Note: This is a schematic representation;
in reality, the density of states varies with E .)

Electrons and holes: the band picture




Filled and empty electron states at 300 K.

(Note: This is a schematic representation;
in reality, the density of states varies with E .)

- * An electron in the conduction band can move to one of the large number of empty states in the conduction band and contribute to a current.

Electrons and holes: the band picture




Filled and empty electron states at 300 K.


(Note: This is a schematic representation;
in reality, the density of states varies with E .)

- * An electron in the conduction band can move to one of the large number of empty states in the conduction band and contribute to a current.
- * Similarly, a hole in the valence band can move to one of the large number of filled states in the valence band and contribute to a current.

Electrons and holes: the band picture




Electrons and holes: the band picture




- * Filled states in the conduction band (the mobile electrons or simply “electrons”) and empty states in the valence band (the mobile vacancies or “holes”) are confined to a narrow energy range near E_c and E_v , respectively (~ 100 meV at 300 K).

Electrons and holes: the band picture




- * Filled states in the conduction band (the mobile electrons or simply “electrons”) and empty states in the valence band (the mobile vacancies or “holes”) are confined to a narrow energy range near E_c and E_v , respectively (~ 100 meV at 300 K).
- * The actual extent of the conduction or valence band does not affect the electron or hole statistics, and it is a common practice to show the conduction band extending to $+\infty$ and the valence band to $-\infty$.

Electrons and holes: the band picture





- * Filled states in the conduction band (the mobile electrons or simply “electrons”) and empty states in the valence band (the mobile vacancies or “holes”) are confined to a narrow energy range near E_c and E_v , respectively (~ 100 meV at 300 K).
- * The actual extent of the conduction or valence band does not affect the electron or hole statistics, and it is a common practice to show the conduction band extending to $+\infty$ and the valence band to $-\infty$.
- * For simplicity, we will not show vacant states in the conduction band, and filled states in the valence band.

Electrons and holes: the band picture




- * Filled states in the conduction band (the mobile electrons or simply “electrons”) and empty states in the valence band (the mobile vacancies or “holes”) are confined to a narrow energy range near E_c and E_v , respectively (~ 100 meV at 300 K).
- * The actual extent of the conduction or valence band does not affect the electron or hole statistics, and it is a common practice to show the conduction band extending to $+\infty$ and the valence band to $-\infty$.
- * For simplicity, we will not show vacant states in the conduction band, and filled states in the valence band.

Effect of electric field




Effect of electric field




* If the electrostatic potential varies with space, it causes “band bending.”

Effect of electric field




- * If the electrostatic potential varies with space, it causes “band bending.”
- * Since E_c and E_v refer to energy of an electron with a negative charge $-q$,
 $E_c(x) = -q\psi(x) + \text{constant}$, $E_v(x) = E_c(x) - E_g$.




- * If the electrostatic potential varies with space, it causes “band bending.”
- * Since E_c and E_v refer to energy of an electron with a negative charge $-q$,
 $E_c(x) = -q\psi(x) + \text{constant}$, $E_v(x) = E_c(x) - E_g$.
- * The electric field and potential are related by $\mathcal{E} = -\frac{d\psi}{dx}$.

$$\rightarrow \mathcal{E} = \frac{1}{q} \frac{dE_c}{dx} = \frac{1}{q} \frac{dE_v}{dx}$$




- * If the electrostatic potential varies with space, it causes “band bending.”
- * Since E_c and E_v refer to energy of an electron with a negative charge $-q$,
 $E_c(x) = -q\psi(x) + \text{constant}$, $E_v(x) = E_c(x) - E_g$.
- * The electric field and potential are related by $\mathcal{E} = -\frac{d\psi}{dx}$.
$$\rightarrow \mathcal{E} = \frac{1}{q} \frac{dE_c}{dx} = \frac{1}{q} \frac{dE_v}{dx}$$
- * The constant in the above equation is irrelevant because only differences such as $(E_c(x_1) - E_c(x_2))$ are important, and the constant drops out.


Energy gap and conductivity



Insulator




Semiconductor




Metal


Material	E_g (eV)	σ ($\Omega\text{-cm}$) ⁻¹
Diamond	5	$\sim 10^{-15}$
Silicon	1.1	$\sim 10^{-5}$
Copper	-	6×10^5



Insulator



Semiconductor




Metal


Material	E_g (eV)	σ ($\Omega\text{-cm}$) ⁻¹
Diamond	5	$\sim 10^{-15}$
Silicon	1.1	$\sim 10^{-5}$
Copper	-	6×10^5

* The electrical conductivity of a crystalline material depends on its energy gap E_g .


Energy gap and conductivity




- * The electrical conductivity of a crystalline material depends on its energy gap E_g .
- * In an insulator, E_g is so large that there are no electrons (in the conduction band) or holes (in the valence band) at room temperature \rightarrow low conductivity.




- * The electrical conductivity of a crystalline material depends on its energy gap E_g .
- * In an insulator, E_g is so large that there are no electrons (in the conduction band) or holes (in the valence band) at room temperature \rightarrow low conductivity.
- * In a metal, E_g is either very small or non-existent. As a result, electrons in the filled states can move to one of the large number of vacant states \rightarrow high conductivity.



Insulator




Semiconductor




Metal


Material	E_g (eV)	σ ($\Omega\text{-cm}$) ⁻¹
Diamond	5	$\sim 10^{-15}$
Silicon	1.1	$\sim 10^{-5}$
Copper	-	6×10^5



Insulator




Semiconductor



Metal



Material	E_g (eV)	σ ($\Omega\text{-cm}$) ⁻¹
Diamond	5	$\sim 10^{-15}$
Silicon	1.1	$\sim 10^{-5}$
Copper	-	6×10^5

- * For a semiconductor, the situation is between these two extremes \rightarrow moderate conductivity.





- * For a semiconductor, the situation is between these two extremes \rightarrow moderate conductivity.
- * Note that we have only looked at an “intrinsic” semiconductor. With addition of appropriate impurity (donor or acceptor) atoms, the conductivity of a semiconductor can be changed very significantly.

Band picture: effect of a donor atom





Band picture: effect of a donor atom




- * When a silicon atom is replaced with a donor (group V) atom, it introduces an energy level (state) in the forbidden gap, which is close to E_c .

Band picture: effect of a donor atom





- * When a silicon atom is replaced with a donor (group V) atom, it introduces an energy level (state) in the forbidden gap, which is close to E_c .
- * At low temperatures, the donor state is occupied, i.e., the electron is bound to the donor atom.

Band picture: effect of a donor atom




- * When a silicon atom is replaced with a donor (group V) atom, it introduces an energy level (state) in the forbidden gap, which is close to E_c .
- * At low temperatures, the donor state is occupied, i.e., the electron is bound to the donor atom.
- * At high temperatures, the electron can cross the energy barrier ($E_c - E_d$) and enter the conduction band.

Band picture: effect of an acceptor atom




Band picture: effect of an acceptor atom




- * When a silicon atom is replaced with an acceptor (group III) atom, it introduces an energy level (state) in the forbidden gap, which is close to E_v .

Band picture: effect of an acceptor atom





- * When a silicon atom is replaced with an acceptor (group III) atom, it introduces an energy level (state) in the forbidden gap, which is close to E_v .
- * At low temperatures, the acceptor state is empty, i.e., there is a vacancy around the acceptor atom.

Band picture: effect of an acceptor atom




- * When a silicon atom is replaced with an acceptor (group III) atom, it introduces an energy level (state) in the forbidden gap, which is close to E_v .
- * At low temperatures, the acceptor state is empty, i.e., there is a vacancy around the acceptor atom.
- * At high temperatures, an electron from the valence band can cross the energy barrier ($E_a - E_v$), leaving a hole in the valence band.

Donor and acceptor levels




Donor and acceptor levels




- * The effectiveness of a donor atom to contribute an electron depends on the binding energy $E_B = E_c - E_d$.

Donor and acceptor levels




- * The effectiveness of a donor atom to contribute an electron depends on the binding energy $E_B = E_c - E_d$.
- * For a “shallow” donor, this energy is typically a few tens of meV (45 meV for P and 54 meV for As in silicon).

Donor and acceptor levels



- * The effectiveness of a donor atom to contribute an electron depends on the binding energy $E_B = E_c - E_d$.
- * For a “shallow” donor, this energy is typically a few tens of meV (45 meV for P and 54 meV for As in silicon).
- * Similarly, the effectiveness of an acceptor atom to contribute a hole depends on the binding energy $E_B = E_a - E_v$.

Donor and acceptor levels



- * The effectiveness of a donor atom to contribute an electron depends on the binding energy $E_B = E_c - E_d$.
- * For a “shallow” donor, this energy is typically a few tens of meV (45 meV for P and 54 meV for As in silicon).
- * Similarly, the effectiveness of an acceptor atom to contribute a hole depends on the binding energy $E_B = E_a - E_v$.
- * For a “shallow” acceptor, this energy is typically a few tens of meV (45 meV for B in silicon).